

PHILIPPINE BIDDING DOCUMENTS

(Procurement of INFRASTRUCTURE PROJECTS)

FOR

INSTALLATION OF CYLINDRICAL TANK FOR HYDROTOR USED OIL

P.R. No.: MG-A5M22-165

Contracts Management Office Logistics Division

> Sixth Edition July 2020 Rev. I

TABLE OF CONTENTS

(₅)	JOSSA	RY OF	. 4
TE	RMS,	ABBREVIATIONS, AND ACRONYMS	. 4
SE	CTIO	N. I. INVITATION TO BID	. 7
SE	CTIO	N II. INSTRUCTIONS TO BIDDERS	11
	Ī.	Scope of Bid	12
	2.	Funding Information	12
	3.	Bidding Requirements	12
	4.	Corrupt, Fraudulent, Collusive, Coercive, and Obstructive Practices	13
	5.	Eligible Bidders	13
	6.	Origin of Associated Goods	13
	7.	Subcontracts	13
	8.	Pre-Bid Conference	14
	9.	Clarification and Amendment of Bidding Documents	14
	IÒ.	Documents Comprising the Bid: Eligibility and Technical Components	14
	ΪĪ.	Documents Comprising the Bid: Financial Component	15
	12.	Alternative Bids	15
	13.	Bid Prices	15
	14.	Bid and Payment Currencies	15
	15.	Bid Security	15
	16.	Sealing and Marking of Bids	16
	17.	Deadline for Submission of Bids	16
	18.	Opening and Preliminary Examination of Bids	16
	19.	Detailed Evaluation and Comparison of Bids	16
	20.	Post Qualification	17
	21.	Signing of the Contract	17
SE	CTION	III. BID DATA SHEET	18
SE	CTION	IV. GENERAL CONDITIONS OF CONTRACT	22
	1.	Scope of Contract.	23
	2.	Sectional Completion of Works	23
	3.,	Possession of Site	23
	4.	The Contractor's Obligations	
	5.	Performance Security	24

6.	Site Investigation Reports	24
7.	Warranty	24
8.	Liability of the Contractor	24
9.	Termination for Other Causes	24
10.	Dayworks	25
Ħ.	Program of Work	25
12.	Instructions, Inspections and Audits	25
13.	Advance Payment	25
14.	Progress Payments	26
15.	Operating and Maintenance Manuals	26
SECTIO:	N V. SPECIAL CONDITIONS OF CONTRACT	27
SECTION	N VI. SPECIFICATIONS	29
SECTION	N VII. Drawings	60
SECTION	N VIII. BILL OF QUANTITIES	66
SECTION	NIX. CHECKLIST OF TECHNICAL AND FINANCIAL DOCUMENTS	70
FORM	OF BID SECURITY (SURETY BOND)	77
CONTR	RACTOR'S ORGANIZATIONAL CHART FOR THE	
	NTRACT	
TNIOL	VENTURE AGREEMENT	94
BID FO	RM	96
	ARY SHEETS OF MATERIALS PRICES, LABOR RATES	99

Glossary of Terms, Abbreviations, and Acronyms

ABC -Approved Budget for the Contract.

ARCC - Allowable Range of Contract Cost.

BAC - Bids and Awards Committee.

Bid – A signed offer or proposal to undertake a contract submitted by a bidder in response to and in consonance with the requirements of the bidding documents. Also referred to as *Proposal* and *Tender*. (2016 revised IRR, Section 5[c])

Bidder – Refers to a contractor, manufacturer, supplier, distributor and/or consultant who submits a bid in response to the requirements of the Bidding Documents. (2016 revised IRR, Section 5[d])

Bidding Documents – The documents issued by the Procuring Entity as the bases for bids, furnishing all information necessary for a prospective bidder to prepare a bid for the Goods, Infrastructure Projects, and/or Consulting Services required by the Procuring Entity. (2016 revised IRR, Section 5[e])

BIR - Bureau of Internal Revenue.

BSP – BangkoSentralngPilipinas.

CDA - Cooperative Development Authority.

Consulting Services – Refer to services for Infrastructure Projects and other types of projects or activities of the GOP requiring adequate external technical and professional expertise that are beyond the capability and/or capacity of the GOP to undertake such as, but not limited to: (i) advisory and review services; (ii) pre-investment or feasibility studies; (iii) design; (iv) construction supervision; (v) management and related services; and (vi) other technical services or special studies. (2016 revised IRR, Section 5[i])

Contract – Refers to the agreement entered into between the Procuring Entity and the Supplier or Manufacturer or Distributor or Service Provider for procurement of Goods and Services; Contractor for Procurement of Infrastructure Projects; or Consultant or Consulting Firm for Procurement of Consulting Services; as the case may be, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.

Contractor – is a natural or juridical entity whose proposal was accepted by the Procuring Entity and to whom the Contract to execute the Work was awarded. Contractor as used in these Bidding Documents may likewise refer to a supplier, distributor, manufacturer, or consultant.

CPI - Consumer Price Index.

DOLE - Department of Labor and Employment.

DTI - Department of Trade and Industry.

Foreign-funded Procurement or Foreign-Assisted Project –Refers to procurement whose funding source is from a foreign government, foreign or international financing institution as specified in the Treaty or International or Executive Agreement. (2016 revised IRR. Section 5[b]).

GFI - Government Financial Institution.

GOCC -Government-owned and/or -controlled corporation.

Goods – Refer to all items, supplies, materials and general support services, except Consulting Services and Infrastructure Projects, which may be needed in the transaction of public businesses or in the pursuit of any government undertaking, project or activity, whether in the nature of equipment, furniture, stationery, materials for construction, or personal property of any kind, including non-personal or contractual services such as the repair and maintenance of equipment and furniture, as well as trucking, hauling, janitorial, security, and related or analogous services, as well as procurement of materials and supplies provided by the Procuring Entity for such services. The term "related" or "analogous services" shall include, but is not limited to, lease or purchase of office space, media advertisements, health maintenance services, and other services essential to the operation of the Procuring Entity. (2016 revised IRR, Section 5[r])

GOP - Government of the Philippines.

Infrastructure Projects – Include the construction, improvement, rehabilitation, demolition, repair, restoration or maintenance of roads and bridges, railways, airports, seaports, communication facilities, civil works components of information technology projects, irrigation, flood control and drainage, water supply, sanitation, sewerage and solid waste management systems, shore protection, energy/power and electrification facilities, national buildings, school buildings, hospital buildings, and other related construction projects of the government. Also referred to as *civil works or works*. (2016 revised IRR, Section 5[u])

LGUs - Local Government Units.

NFCC - Net Financial Contracting Capacity.

NGA - National Government Agency.

PCAB - Philippine Contractors Accreditation Board.

PhilGEPS - Philippine Government Electronic Procurement System.

Procurement Project – refers to a specific or identified procurement covering goods, infrastructure project or consulting services. A Procurement Project shall be described, detailed, and scheduled in the Project Procurement Management Plan prepared by the agency which shall be consolidated in the procuring entity's Annual Procurement Plan. (GPPB Circular No. 06-2019 dated 17 July 2019)

PSA - Philippine Statistics Authority.

SEC - Securities and Exchange Commission.

 ${\bf SLCC-Single\ Largest\ Completed\ Contract}.$

UN - United Nations.

BID DOCUMENTS

SECTION I- INVITATION TO BID

NAME OF PROJECT: INSTALLATION OF CYLINDRICAL TANK FOR HYDROTOR USED OIL

PR NO /REF NO MG-A5M22-165 /INFRA2022-AG5-052

Section I. Invitation to Bid

M

PR NO./REF. NO.: MG-A5M22-165 /INFRA2022-AG5-052

SECTION I- INVITATION TO BID



Invitation to Bid for Installation of Cylindrical Tank for Hydrotor Used Oil

The NATIONAL POWER CORPORATION—MINDANAO GENERATION, through the approved Corporate Budget of NPC for CY 2022intends to apply the sum of One Million Three Hundred Thousand Pesos (PHP 1,300,000.00) being the Approved Budget for the Contract (ABC) to payments under the contract for Installation of Cylindrical Tank for Hydrotor Used Oil at NPC MinGen, Nangka, balo-I, Lanao del Norte (INFRA2022-AG5-052). Bids received in excess of the ABC shall be automatically rejected at bid opening.

- The NATIONAL POWER CORPORATION-MINDANAO GENERATION now invites bids for the above Procurement Project. Completion of the Works is required Eighty (80) calendar days. Bidders should have completed a contract similar to the Project. The description of an eligible bidder is contained in the Bidding Documents, particularly, in Section II (Instructions to Bidders).
- Bidding will be conducted through open competitive bidding procedures using nondiscretionary "pass/fail" criterion as specified in the 2016 revised Implementing Rules and Regulations (IRR) of Republic Act (RA) No. 9184.
- Interested bidders may obtain further information from BAC Secretariat, NATIONAL POWER CORPORATION-MINDANAO GENERATION and inspect the Bidding Documents at the address given below from 8:00 AM - 5:00 PM Monday to Friday.
- 4. A complete set of Bidding Documents may be acquired by interested Bidders <u>August 3 23, 2022</u> from the given address and website(s) below and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of <u>Three Thousand Pesos (PHP3,000.00)</u>. The Procuring Entity shall allow the bidder to pay online and present its proof of payment for the fees in person, by facsimile, or through electronic means. For those prospective bidders who wish to pay online, below are the details of the account:

LandbankAccount name

NPC GENCO 5 COLLECTIONS FUND

LandbankAccount number

0321-1689-14

It may also be downloaded free of charge from the website of the Philippine Government Electronic Procurement System (PhilGEPS) provided that Bidders shall

SECTION I- INVITATION TO BID

PR NO //REF. NO. MG-A5M22-165 //NFRA2022-AG5-052

pay the applicable fee for the Bidding Documents not later than the submission of their bids.

- 5. The NATIONAL POWER CORPORATION—MINDANAO GENERATION will hold a Pre-Bid Conference on August 11, 2022 at 9:00 AM at Bidding Room, NPC-Mindanao Generation Headquarters, Maria Cristina, Iligan City and/or through videoconferencing/webcasting via ZOOM, which shall be open to prospective bidders. Interested online attendees are required to pre-register one (1) day before the scheduled pre-bidding conference. For pre-registration, contact tel. no. (063)-222-3459 or email logistics afd mingen@napocor.gov.ph.
- Bids must be duly received by the BAC Secretariat through manual submission at the
 office address as indicated below, on or before August 23, 2022 at 9:30 AM. Late bids
 shall not be accepted.
- All bids must be accompanied by a bid security in any of the acceptable forms and in the amount stated in ITB Clause 15.
- Bid opening shall be on August 23, 2022 at 9:30 AM at the Bidding Room, NPC-Mindanao Generation Headquarters, Maria Cristina, Iligan City. Bids will be opened in the presence of the bidders' representatives who choose to attend the activity.
- 9. This project requires submission of at least:
 - Certificate of Site Inspection

Ň

- 10. The NATIONAL POWER CORPORATION—MINDANAO GENERATION reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35.6 and 41 of the 2016 revised Implementing Rules and Regulations (IRR) of RA No. 9184, without thereby incurring any liability to the affected bidder or bidders.
- 11. For further information, please refer to:

BAC Secretariat

Contracts Management Office
Logistics Division
Mindanao Generation Headquarters
National Power Corporation
Maria Cristina, Iligan City
logistics_afd_mingen@napocor.gov.ph
Tel. No.: (063)222-3459

Fax No.: (063)223-8355/(063)223-4604

www.napocor.gov.ph

SECTION I- INVITATION TO BID

PR NO./REF. NO. MG-A5M22-165 /INFRA2022-AG5-052

12. You may visit the following websites:

For downloading of Bidding Documents: https://www.philgeps.gov.ph/ or https://www.philgeps.gov.ph/ or https://www.philgeps.gov.ph/

REYNANTE T. CIRUELA
Chairman, Bids and Awards Committee
Mindanao Generation Headquarters

Date of PhilGEPS Publication: 03 August 2022

LIST OF PRIVATE SURETY COMPANIES ACCEPTABLE TO NPC AS OF 11 NOVEMBER 2018

Name of Surety Company	Contact No.
ALPHA INSURANCE & SURETY CO., INC.	525-1301
Alpha Insurance Centre	F - 522-6131
1025 San Marcelino St., Ermita, Manila	_ 1
COMMONWEALTH INSURANCE COMPANY	818-7626 loc 1253
10/12F, BDO Plaza, 8737 Paseo de Roxas	813-2685
Makati City	
COUNTRY BANKERS INSURANCE CORPORATION	524-0621 to 23
Country Bankers Centre, 648 T. M. Kalaw Avenue	
Ermita, Manila	
INTRA STRATA ASSURANCE CORP.	817-3031 to 34
8th Floor, 88 Corporate Center Building	
Sedeño cor. Valero St., Salcedo Vill, Makati City	
LIBERTY INSURANCE CORPORATION	819-1961 to 66
JCS Building, 119 Dela Rosa cor. Carlos Palanca Sts.	
Legaspi Village, Makati City	
PACIFIC UNION INSURANCE COMPANY	845-1033 to 37
Unit 2401 Antel Corporate Center 121 Valero St.	
Salcedo Village, Makati City	
PRUDENTIAL GUARANTEE & ASSURANCE, INC.	810-4916 to 35
Coyuito House, 119 Palanca St.	
Legaspi Village, Makati City	
STERLING INSURANCE COMPANY, INC.	759-3082/759-2930/
6F Zeta Annex II Building	759-2921/
191 Salcedo St., Legaspi Village, Makati City	892-3792
THE MERCANTILE INSURANCE CO. LTD.	527-7701 to 20
Mercantile Insurance Building	
Corner General Luna & Beaterio Sts. Intramuros, Manila	
TRAVELLERS INSURANCE SURETY CORPORATION	521-3822/400-9327
10th Floor, G. E. Antonio Building	43
T.M. Kalaw corner J. Bocobo St., Ermita, Manila	* 3
WESTERN GUARANTEE CORPORATION	241-7401/242-1073
Suite 508 BPI Office Condominium	
Plaza Cervantes, Binondo, Manila	1

Note: Indicate in the performance, advance payment, retention and guarantee bond the following NPC Standard Terms & Conditions:

- The bond is a penal bond, callable on demand and the entire amount thereof shall be forfeited in favor of the Obligee upon default of the Principal without the need to prove or to show grounds or reasons for demand for the sum specified therein;
- The amount claimed by the Obligee under this bond shall be paid in full and shall never be subject to any adjustment by the Surety;
- In case of claim, the Surety shall pay such claim within sixty (60) days from receipt by the Surety of the Obligee's notice of claim/demand letter notwithstanding any objection thereto by the Principal.
- 4.) The proposed bond is valid until the immance of NPC of the Curt. of Final Acceptance.

SECTION II- INSTRUCTION TO BIDDERS

FR NO IREF NO MG-A5M22-105/INFRA2020-AG5-052

Section II. Instructions to Bidders

Ţ

PR NOVREE NO MG-ASM22-165/INFRAZ020-AG5-052

1. Scope of Bid

The Procuring Entity, NATIONAL POWER CORPORATION-MINDANAO GENERATION invites Bids for the Installation of Cylindrical Tank for Hyhdrotor Used Oil, NPC MinGen, Nangka, balo-I, Lanuo del Norte, with Project Identification NumberINFRA2022-AG5-052.

The Procurement Project (referred to herein as "Project") is for the construction of Works, as described in Section VI (Specifications).

2. Funding Information

- The GOP through the source of funding as indicated below for CY 2022in the amount of One MillionThree Hundred ThousandPesos (PHP1,300,000.00)
- 2.2. The source of funding is:
 - GOCC and GFIs, the proposed Corporate Operating Budget.

3. Bidding Requirements

The Bidding for the Project shall be governed by all the provisions of RA No. 9184 and its 2016 revised IRR, including its Generic Procurement Manual and associated policies, rules and regulations as the primary source thereof, while the herein clauses shall serve as the secondary source thereof.

Any amendments made to the IRR and other GPPB issuances shall be applicable only to the ongoing posting, advertisement, or invitation to bid by the BAC through the issuance of a supplemental or bid bulletin.

The Bidder, by the act of submitting its Bid, shall be deemed to have inspected the site, determined the general characteristics of the contracted Works and the conditions for this Project, such as the location and the nature of the work; (b) climatic conditions; (c) transportation facilities; (c) nature and condition of the terrain, geological conditions at the site communication facilities, requirements, location and availability of construction aggregates and other materials, labor, water, electric power and access roads; and (d) other factors that may affect the cost, duration and execution or implementation of the contract, project, or work and examine all instructions, forms, terms, and project requirements in the Bidding Documents.

PRINO//REF NO MG-A5M22-165/INFRAZU20-AG5-052

4. Corrupt, Fraudulent, Collusive, Coercive, and Obstructive Practices

The Procuring Entity, as well as the Bidders and Contractors, shall observe the highest standard of ethics during the procurement and execution of the contract. They or through an agent shall not engage in corrupt, fraudulent, collusive, coercive, and obstructive practices defined under Annex "I" of the 2016 revised IRR of RA No. 9184 or other integrity violations in competing for the Project.

5. Eligible Bidders

- Only Bids of Bidders found to be legally, technically, and financially capable will be evaluated.
- 5.2. The Bidder must have an experience of having completed a Single Largest Completed Contract (SLCC) that is similar to this Project, equivalent to at least fifty percent (50%) of the ABC adjusted, if necessary, by the Bidder to current prices using the PSA's CPI, except under conditions provided for in Section 23.4.2.4 of the 2016 revised IRR of RA No. 9184.
 - A contract is considered to be "similar" to the contract to be bid if it has the major categories of work stated in the BDS.
- 5.3. For Foreign-funded Procurement, the Procuring Entity and the foreign government/foreign or international financing institution may agree on another track record requirement, as specified in the Bidding Document prepared for this purpose.
- The Bidders shall comply with the eligibility criteria under Section 23.4.2 of the 2016 IRR of RA No. 9184.

6. Origin of Associated Goods

There is no restriction on the origin of Goods other than those prohibited by a decision of the UN Security Council taken under Chapter VII of the Charter of the UN.

7. Subcontracts

7.1. The Bidder may subcontract portions of the Project to the extent allowed by the Procuring Entity as stated herein, but in no case more than fifty percent (50%) of the Project.

The Procuring Entity has prescribed that:

a. Subcontracting is not allowed.

PRINO/IREF NO MG-A5M22-165/INFRA2020-AG5-052

8. Pre-Bid Conference

The Procuring Entity will hold a pre-bid conference for this Project on the specified date and time and either at its physical address and/or through videoconferencing/webcasting as indicated in paragraph 6 of the IB.

9. Clarification and Amendment of Bidding Documents

Prospective bidders may request for clarification on and/or interpretation of any part of the Bidding Documents. Such requests must be in writing and received by the Procuring Entity, either at its given address or through electronic mail indicated in the IB, at least ten (10) calendar days before the deadline set for the submission and receipt of Bids.

10. Documents Comprising the Bid: Eligibility and Technical Components

- The first envelope shall contain the eligibility and technical documents of the Bid as specified in Section IX. Checklist of Technical and Financial Documents.
- 10.2. If the eligibility requirements or statements, the bids, and all other documents for submission to the BAC are in foreign language other than English, it must be accompanied by a translation in English, which shall be authenticated by the appropriate Philippine foreign service establishment, post, or the equivalent office having jurisdiction over the foreign bidder's affairs in the Philippines. For Contracting Parties to the Apostille Convention, only the translated documents shall be authenticated through an apostille pursuant to GPPB Resolution No. 13-2019 dated 23 May 2019. The English translation shall govern, for purposes of interpretation of the bid.
- 10.3. A valid PCAB License is required, and in case of joint ventures, a valid special PCAB License, and registration for the type and cost of the contract for this Project. Any additional type of Contractor license or permit shall be indicated in the BDS.
- 10.4. A List of Contractor's key personnel (e.g., Project Manager, Project Engineers, Materials Engineers, and Foremen) assigned to the contract to be bid, with their complete qualification and experience data shall be provided. These key personnel must meet the required minimum years of experience set in the BDS.
- 10.5. A List of Contractor's major equipment units, which are owned, leased, and/or under purchase agreements, supported by proof of ownership, certification of availability of equipment from the equipment lessor/vendor for the duration of the project, as the case may be, must meet the minimum requirements for the contract set in the BDS.

11. Documents Comprising the Bid: Financial Component

- 11.1. The second bid envelope shall contain the financial documents for the Bid as specified in Section IX. Checklist of Technical and Financial Documents.
- 11.2. Any bid exceeding the ABC indicated in paragraph 1 of the IB shall not be accepted.
- 11.3. For Foreign-funded procurement, a ceiling may be applied to bid prices provided the conditions are met under Section 31.2 of the 2016 revised IRR of RA No. 9184.

12. Alternative Bids

Bidders shall submit offers that comply with the requirements of the Bidding Documents, including the basic technical design as indicated in the drawings and specifications. Unless there is a value engineering clause in the BDS, alternative Bids shall not be accepted.

13.Bid Prices

All bid prices for the given scope of work in the Project as awarded shall be considered as fixed prices, and therefore not subject to price escalation during contract implementation, except under extraordinary circumstances as determined by the NEDA and approved by the GPPB pursuant to the revised Guidelines for Contract Price Escalation guidelines.

14.Bid and Payment Currencies

- 14.1. Bid prices may be quoted in the local currency or tradeable currency accepted by the BSP at the discretion of the Bidder. However, for purposes of bid evaluation, Bids denominated in foreign currencies shall be converted to Philippine currency based on the exchange rate as published in the BSP reference rate bulletin on the day of the bid opening.
- 14.2. Payment of the contract price shall be made in:
 - a. Philippine Pesos.

15. Bid Security

- 15.1. The Bidder shall submit a Bid Securing Declaration or any form of Bid Security in the amount indicated in the BDS, which shall be not less than the percentage of the ABC in accordance with the schedule in the BDS.
- 15.2. The Bid and bid security shall be valid until *One Hundred Twenty (120)*Calendar Days from the Scheduled Bid Opening. Any bid not accompanied

PR NO/REF NO MG-A5M22-165/INFRA2020-AG5-052

by an acceptable bid security shall be rejected by the Procuring Entity as non-responsive.

16. Sealing and Marking of Bids

Each Bidder shall submit one copy of the first and second components of its Bid.

The Procuring Entity may request additional hard copies and/or electronic copies of the Bid. However, failure of the Bidders to comply with the said request shall not be a ground for disqualification.

If the Procuring Entity allows the submission of bids through online submission to the given website or any other electronic means, the Bidder shall submit an electronic copy of its Bid, which must be digitally signed. An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.

17. Deadline for Submission of Bids

The Bidders shall submit on the specified date and time and either at its physical address or through online submission as indicated in paragraph 7 of the IB.

18. Opening and Preliminary Examination of Bids

- 18.1. The BAC shall open the Bids in public at the time, on the date, and at the place specified in paragraph 9 of the IB. The Bidders' representatives who are present shall sign a register evidencing their attendance. In case videoconferencing, webcasting or other similar technologies will be used, attendance of participants shall likewise be recorded by the BAC Secretariat.
 - In case the Bids cannot be opened as scheduled due to justifiable reasons, the rescheduling requirements under Section 29 of the 2016 revised IRR of RA No. 9184 shall prevail.
- 18.2. The preliminary examination of Bids shall be governed by Section 30 of the 2016 revised IRR of RA No. 9184.

19. Detailed Evaluation and Comparison of Bids

- 19.1. The Procuring Entity's BAC shall immediately conduct a detailed evaluation of all Bids rated "passed" using non-discretionary pass/fail criteria. The BAC shall consider the conditions in the evaluation of Bids under Section 32.2 of 2016 revised IRR of RA No. 9184.
- 19.2. If the Project allows partial bids, all Bids and combinations of Bids as indicated in the BDS shall be received by the same deadline and opened and evaluated simultaneously so as to determine the Bid or combination of Bids

PR NO //REF, NO. MG-A5M22-165/INFRA2020-AG5-052

offering the lowest calculated cost to the Procuring Entity. Bid Security as required by ITB Clause 16 shall be submitted for each contract (lot) separately.

19.3. In all cases, the NFCC computation pursuant to Section 23.4.2.6 of the 2016 revised IRR of RA No. 9184 must be sufficient for the total of the ABCs for all the lots participated in by the prospective Bidder.

20. Post Qualification

Within a non-extendible period of five (5) calendar days from receipt by the Bidder of the notice from the BAC that it submitted the Lowest Calculated Bid, the Bidder shall submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS), and other appropriate licenses and permits required by law and stated in the BDS.

21. Signing of the Contract

The documents required in Section 37.2 of the 2016 revised IRR of RA No. 9184 shall form part of the Contract. Additional Contract documents are indicated in the BDS.

Section III. Bid Data Sheet

Ť

PRIND /REF NO. MG-A5M22-165 / INFRA2020-AG5-052

Bid Data Sheet

ITB Clause		- <u></u> -				
5.2		cts similar to the Project in es of work, which shall be	refer to contracts which have			
7.1	Subcontracting is not all	owed.				
10.3	None					
10.4	The key personnel must meet the required minimum years of experience below:					
	Key Personnel 1 - Project Engineer	General Expertise Licensed Civil Engineer	Relevant Experience At least five (5) years experience in related works			
	1 - Construction Foreman	B.S. Civil Engineering Graduate	At least three (3) years experience in similar works			
		Civil Engineering Technology Graduate T Non-graduate	At least five (5) years experience in similar works At least five (5) years working experience as Construction Foreman in similar works			
	1 - Construction Safety and Health Officer (SO2)	Construction Safety Officer 2	At least forty (40) hours of Construction Safety and Health (COSH) Training from Occupational Safety and Health Center (OSHC) or Safety Training Organizations (STOs) accredited by the Department of Labor and Employment (DOLE). Must be present during the whole duration of the project)			
	2 - Welders	NCII	At least three (3) years experience in welding/culting works			

li .			
	1) Valid Professional Regulation Commission (PRC) license for professional personnel; (2) Certificate of Training with accreditation from DOLE for the Construction Safety & Health Officer; (3) TESDA Training Certificate (NC II) of Welders, Electrician, Plumbers & etc. (if applicable); and (4) Diploma and/or Service Record/Certificate of Employment of previous and/or current employer for Project Engineer, Safety Officer. Construction Foreman, Welders. Electrician & Plumber, etc. (if applicable) shall be submitted and included as an attachment in the Standard Form NPCMGNSF-INFR-05: List of Key personnel Proposed to be Assigned to the Contract.		
	Project Engineer or Foreman and Construction Safety & Health Officer maybe one person, as long as he meets the requirements of the two positions. Provided however, that there is no overlapping of projects undertaken by the same contractor and supervised by the same person.		
	The above key personnel must be either employed by the applicant or contracted by the applicant to be employed for the contract to be bid.		
10.5	The minimum equipment requirements are the following:		
	EquipmentCapacityNumber of UnitsWelding Machine7300 AmpTwo (2)Concrete Mixer1-baggerOne (1)Mini Dump Truck3.0 cu.m.One (1)Oxy/Acetylene withN/AOne (1)Tanks		
12	N/A		
15.1	The bid security shall be in the form of a Bid Securing Declaration or any of the following forms and amounts: a. The amount of not less than PHP 26,000.00(2% of ABC), if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; b. The amount of not less than PHP 65,000.00 (5% of ABC), if bid security is in Surety Bond.		
19.2	Partial bids are allowed, as follows:		
20	Additional documents to be submitted during Post-Qualification: 1. Other appropriate licenses and permits required by law and stated in the Bidding documents. a. Original Bank Statement year ending prior to bid opening, b. Valid and updated PhilGEPS Registration (Platinum Membership)		
	(all pages);		

PR NO /REF NO MG-A5M22-165 / INFRA2020-AG5-052

	c. Registration Certificate from Securities and Exchange Commission (SEC), Department of Trade and Industry (DTI) for sole proprietorship, or Cooperative Development Authority (CDA) for cooperatives or its equivalent document; d. Mayor's or Business permit issued by the city or municipality where the principal place of business of the prospective bidder is located, or the equivalent document for Exclusive Economic Zones or Areas; e. Valid Tax clearance per E.O. No. 398, s. 2005, as finally reviewed and approved by the Bureau of Internal Revenue (BIR). Quarterly Income Tax Returns filed and paid through the BIR Electronic Filing and Payment System (eFPS); f. The prospective bidder's audited financial statements, showing, among others, the prospective bidder's total and current assets and liabilities, stamped "received" by the BIR or its duly accredited and authorized institutions, for the preceding calendar year which should not be earlier than two (2) years from the date of bid submission; g. Philippine Contractors Accreditation Board (PCAB) License; h. Board of Accountancy (BOA) Certificate; Contract and/or Notice of Award as supporting documents for NPC MinGen Form No. NPCMGNSF-INFR-01, if applicable; Certificate of Site Inspection issued by Plant/Department Manager or his authorized representative.
21	Additional contract documents relevant to the Project that may be required by existing laws and/or the Procuring Entity, <u>prior to contract signing</u> , such as: a) Approved construction schedule and S-curve b) Approved manpower schedule c) Construction methods d) Approved equipment utilization schedule e) Construction safety and health program approved by the DOLE f) Approved Project Evaluation Review Technique/Critical Path Method (PERT/CPM)

PR NO/REF NO MG-A5M22-165 / INFRA2020-AG5-052

Section IV. General Conditions of Contract

T

PR NO./REF. NO. MG-A5M22-165 / INFRA2020-AG5-052

1. Scope of Contract

This Contract shall include all such items, although not specifically mentioned, that can be reasonably inferred as being required for its completion as if such items were expressly mentioned herein. All the provisions of RA No. 9184 and its 2016 revised IRR, including the Generic Procurement Manual, and associated issuance s, constitute the primary source for the terms and conditions of the Contract, and thus, applicable in contract implementation. Herein clauses shall serve as the secondary source for the terms and conditions of the Contract.

This is without prejudice to Sections 74.1 and 74.2 of the 2016 revised IRR of RA No. 9184 allowing the GPPB to amend the IRR, which shall be applied to all procurement activities, the advertisement, posting, or invitation of which were issued after the effectivity of the said amendment.

2. Sectional Completion of Works

If sectional completion is specified in the **Special Conditions of Contract (SCC)**, references in the Conditions of Contract to the Works, the Completion Date, and the Intended Completion Date shall apply to any Section of the Works (other than references to the Completion Date and Intended Completion Date for the whole of the Works).

T

3. Possession of Site

- 4.1. The Procuring Entity shall give possession of all or parts of the Site to the Contractor based on the schedule of delivery indicated in the SCC, which corresponds to the execution of the Works. If the Contractor suffers delay or incurs cost from failure on the part of the Procuring Entity to give possession in accordance with the terms of this clause, the Procuring Entity's Representative shall give the Contractor a Contract Time Extension and certify such sum as fair to cover the cost incurred, which sum shall be paid by Procuring Entity.
- 4.2. If possession of a portion is not given by the above date, the Procuring Entity will be deemed to have delayed the start of the relevant activities. The resulting adjustments in contract time to address such delay may be addressed through contract extension provided under Annex "E" of the 2016 revised IRR of RA No. 9184.

4. The Contractor's Obligations

The Contractor shall employ the key personnel named in the Schedule of Key Personnel indicating their designation, in accordance with ITB Clause 10.3 and specified in the BDS, to carry out the supervision of the Works.

PR NOJREE NO MG-A5M22-165 / INFRA2020-AG5-052

The Procuring Entity will approve any proposed replacement of key personnel only if their relevant qualifications and abilities are equal to or better than those of the personnel listed in the Schedule.

5. Performance Security

- 5.1. Within ten (10) calendar days from receipt of the Notice of Award from the Procuring Entity but in no case later than the signing of the contract by both parties, the successful Bidder shall furnish the performance security in any of the forms prescribed in Section 39 of the 2016 revised IRR.
- 5.2. The Contractor, by entering into the Contract with the Procuring Entity, acknowledges the right of the Procuring Entity to institute action pursuant to RA No. 3688 against any subcontractor be they an individual, firm, partnership, corporation, or association supplying the Contractor with labor, materials and/or equipment for the performance of this Contract.

6. Site Investigation Reports

The Contractor, in preparing the Bid, shall rely on any Site Investigation Reports referred to in the SCC supplemented by any information obtained by the Contractor.

7. Warranty

- Ţ
- 7.1. In case the Contractor fails to undertake the repair works under Section 62.2.2 of the 2016 revised IRR, the Procuring Entity shall forfeit its performance security, subject its property(ies) to attachment or garnishment proceedings, and perpetually disqualify it from participating in any public bidding. All payables of the GOP in his favor shall be offset to recover the costs.
- 7.2. The warranty against Structural Defects/Failures, except that occasioned-on force majeure, shall cover the period from the date of issuance of the Certificate of Final Acceptance by the Procuring Entity. Specific duration of the warranty is found in the SCC.

8. Liability of the Contractor

Subject to additional provisions, if any, set forth in the SCC, the Contractor's liability under this Contract shall be as provided by the laws of the Republic of the Philippines.

If the Contractor is a joint venture, all partners to the joint venture shall be jointly and severally liable to the Procuring Entity.

9. Termination for Other Causes

PR NO:/REF NO MG-A5M22-165 / INFRA2020-AG5-052

Contract termination shall be initiated in case it is determined *prima facie* by the Procuring Entity that the Contractor has engaged, before, or during the implementation of the contract, in unlawful deeds and behaviors relative to contract acquisition and implementation, such as, but not limited to corrupt, fraudulent, collusive, coercive, and obstructive practices as stated in ITB Clause 4.

10. Dayworks

Subject to the guidelines on Variation Order in Annex "E" of the 2016 revised IRR of RA No. 9184, and if applicable as indicated in the SCC, the Dayworks rates in the Contractor's Bid shall be used for small additional amounts of work only when the Procuring Entity's Representative has given written instructions in advance for additional work to be paid for in that way.

11. Program of Work

- 11.1. The Contractor shall submit to the Procuring Entity's Representative for approval the said Program of Work showing the general methods, arrangements, order, and timing for all the activities in the Works. The submissions of the Program of Work are indicated in the SCC.
- 11.2. The Contractor shall submit to the Procuring Entity's Representative for approval an updated Program of Work at intervals no longer than the period stated in the SCC. If the Contractor does not submit an updated Program of Work within this period, the Procuring Entity's Representative may withhold the amount stated in the SCC from the next payment certificate and continue to withhold this amount until the next payment after the date on which the overdue Program of Work has been submitted.

12. Instructions, Inspections and Audits

The Contractor shall permit the GOP or the Procuring Entity to inspect the Contractor's accounts and records relating to the performance of the Contractor and to have them audited by auditors of the GOP or the Procuring Entity, as may be required.

13.Advance Payment

The Procuring Entity shall, upon a written request of the Contractor which shall be submitted as a Contract document, make an advance payment to the Contractor in an amount not exceeding fifteen percent (15%) of the total contract price, to be made in lump sum, or at the most two installments according to a schedule specified in the SCC, subject to the requirements in Annex "E" of the 2016 revised IRR of RA No. 9184.

14. Progress Payments

The Contractor may submit a request for payment for Work accomplished. Such requests for payment shall be verified and certified by the Procuring Entity's Representative/Project Engineer. Except as otherwise stipulated in the SCC, materials and equipment delivered on the site but not completely put in place shall not be included for payment.

15. Operating and Maintenance Manuals

- 15.1. If required, the Contractor will provide "as built" Drawings and/or operating and maintenance manuals as specified in the SCC.
- 15.2. If the Contractor does not provide the Drawings and/or manuals by the dates stated above, or they do not receive the Procuring Entity's Representative's approval, the Procuring Entity's Representative may withhold the amount stated in the SCC from payments due to the Contractor.

Ť

BID DOCUMENTS

NAME OF PROJECT. INSTALLATION OF CYLINDRIGAL TANK FOR HYDROTOR USED OIL

SECTION V- SPECIAL CONDITIONS OF CONTRACT

PR NO./REF NO MG:A5M22-165 / INFRA2020-AG5-052

Section V. Special Conditions of Contract

PR NO /REF. NO MG-A5M22-165 / INFRA2020-AG5-052

Special Conditions of Contract

GCC Clause	
2	Sectional completion is not specified.
4.1	The Procuring Entity shall give possession of the Site to the Contractor on the start date.
6	The site investigation reports are: NONE
7.2	Fiffeen (15) years
10	Dayworks are not applicable to the contract.
11.1	The Contractor shall submit the Program of Work to the Procuring Entity's Representative <u>upon contract signing</u> or within <u>three (3)</u> days of delivery of the Notice of Award.
11.2	The amount to be withheld for late submission of an updated Program of Work is Fifty (50) %of the billed amount. The updating of Program of Work shall be done bi-monthly.
13	The amount of the advance payment is 15% of contract amount and paid in lump sum.
14	No further instruction.
15.1	The date by which operating and maintenance manuals are required is upon completion of the project. The date by which "as built" drawings are required is upon completion
	of the project.
15.2	The amount to be withheld for failing to produce "as built" drawings and/or operating and maintenance manuals by the date required is one hundred percent (100%) of the final billing.

BID DOCUMENTS

NAME OF PROJECT - INSTALLATION OF CYLINDRICAL TANK FOR HYDROTOR USED OIL

SECTION VI- SPECIFICATIONS

PRING,/REF NO MG-A5M22-165/INFRA2022-AG5-052

Section VI. Specifications

PR NO./REF. NO. MG-A5M22-165/INFRA2022-AG5-052

PROJECT HIGHLIGHTS

PH-1.0 GENERAL

The purpose of this project is to address the problem encountered during replacement of lubricating/hydraulic oil due to unavailability of storage tank fro used and contaminated oil because all oil drums were fully occupied filtered used oil. During last audit conducted by NPC/PSALM it is highly recommended fro the immediate transfer of existing old stock used hydrotor oil to proper storage tank the power cavern area.

PH-2.0 PROJECT LOCATION

The project is located at NPC Agus 4 HE Plant, Nangka, Balo-I, Lanao del Norte

PH-3.0 SCOPE OF WORK

The work and services to be performed by the Contractor for this undertaking shall essentially consist of, but not limited to the following:

- Mobilization/establishment of Contractors complete construction camp and other facilities;
- B. CONSTRUCTION SAFETY AND HEALTH PROGRAM (To provide safety signages, fire extinguisher and PPE's on the whole duration of the project. First ald kit must be present at the site and shall be turned-over to NPC after the completion of the project, if not used.)
- C. PURCHASE (SUPPLY , DELIVERY AND INSTALL) OF FABRICATED CYLINDRICAL TANK, 14,000 LTRS.
- D. SITE CLEARING
- E. LAY-OUT AND STAKING
- F. EXCAVATION WORKS
- G. EMBANKMENT WORKS
- H. CONCRETE WORKS
- I. MASONRY WORKS
- J. STEEL STRUCTURE
- K. FABRICATION WORKS
- L. ROOFING WORKS
- M. PAINTING WORKS
- N. Demobilization including clearing of site/demolition of Contractor's camp facilities.

PH-4.0 CONTRACT PERIOD

The contractor shall complete the works as specified in Clause 3 within **Eighty (80) calendar days**. The total contract duration is inclusive of six (6) unworkable days considered unfavorable for the execution of work at site. The contract period shall be reckoned from the date of contract effectivity as specified in the Notice to Proceed







SECTION VI- SPECIFICATIONS

PR.NO./REF. NO: MG-A5M22-165/INFRA2022-AG5-052

PH-5.0 CONTRACTOR'S CLASSIFICATION

The contractor must have a valid Philippine Contractor's Accreditation Board (PCAB) license of at least Category C or D - General Building with inter-agency registration of at least Small B - Building and Industrial Plant

The contractor must have undertaken similar contracts that involves electrical system and lightning protection system provided that the contract cost shall be at least equivalent to 50% of ABC





PR NO./REF_NO: MG-A5M22-165/INFRA2022-AG5-052

SECTION VI- SPECIFICATIONS

TECHNICAL SPECIFICATIONS

TS - 1.1 Scope

This section covers the construction and/or maintenance of access roads, drainage system and other appurtenant structures, moving-in of the Contractor's construction equipment, setting up of the Contractor's camp and the disposition of the Contractor's various facilities at the end of the Contract.

TS - 1.2 Moving-in

The contractor shall bring to the site all his necessary construction equipment and plant and install all stationary construction equipment and plant at location and in the manner approved by the NPC. The Contractor shall submit sufficient detailed plans showing the proposed location of such stationary equipment and plant and other pertinent data. No installation of such stationary equipment shall be undertaken unless the corresponding plans have been approved by the NPC.

TS - 1.3 Contractor's Camp Facilities

The Contractor shall provide and grade his camp site, construct his camp, employee housing, warehouse, machine and repair shops, fuel storage tanks and provide such related facilities and sanitary conveniences that the Contractor deems necessary for maintaining health, peace and order in the camp and work areas. The areas that may be used by the Contractor within the plant site shall be designated by the NPC.

The Contractor shall provide, maintain and operate, under competent direction, such camps and facilities as are necessary for the housing, feeding and accommodation of his employees.

TS - 1.4 Water Supply


The Contractor shall, at his own expense, be responsible for the supply installation, operation and maintenance of a safe and adequate supply of drinking and domestic water.

TS - 1.5 Sewerage Disposal and Sanitation

The Contractor shall, at his own expense, be responsible for the installation, operation and maintenance of an adequate sewerage disposal and sanitation system and shall provide adequate toilet and wash-up facilities for his employees at his camp and in the areas where work is being carried out.

The Contractor shall execute the work with due regard to adequate sanitary provisions and applicable codes and shall take all necessary steps to prevent the pollution of water in any spring, river, or other





SECTION VI- SPECIFICATIONS

PR NO /REF. NO MG-A5M22-165/INFRA2022-AG5-052

sources of water supply. All toilets or wash-up facilities shall be subject to the prior and continuing approval of the NPC.

TS - 1.6 Fire Protection

The Contractor shall observe all necessary precautions against fire, shall provide and maintain at his own expense, portable fire-fighting equipment he may deem necessary, and shall comply with all applicable laws of the Philippines relating thereto.

In the event of an uncontrollable fire occurring in the area of the Contractor's operation, the Contractor shall have to extinguish the fire immediately at his own expense, to the full extent of the manpower and equipment employed under the contract at the time of the fire.

The Contractor shall indemnify NPC against all liabilities, claims, damages and/or lawsuits arising thereto.

TS - 1.7 Construction Power

The Construction shall be responsible for providing his own electric power supply required for construction and erection/installation. If power is available from NPC and should the Contractor elect to utilize the NPC's power supply, he shall make an arrangement with NPC concerned group as to the billing rates and other requirements needed for direct connection to NPC.

TS - 1.8 Camp Security

The Contractor shall provide his own security force to the extent that he deems necessary for maintaining peace and order in the camp and work areas and to safeguard materials and equipment. Nothing under the provisions of this paragraph shall relieve the Contractor from full responsibility for the maintenance of peace and order and protection of life and property in all areas where he operates.

TS - 1.9 Construction Material Storage

The Contractor is required to put up warehouse(s) with capacities sufficient to store the construction materials required in the work, the warehouse(s) shall be specifically for this contract, notwithstanding his other facilities in the site that may serve the purpose.

TS - 1.10 Removal of Camp and Construction Facilities

After the completion of the work covered by the contract and prior to acceptance of the completed work, the entire camp facilities of the Contractor, including its water supply system, electric distribution system, quarters, warehouses, shops, dining halls, commissaries, temporary shed and other facilities therein shall be removed by the Contractor. The site shall be cleared and cleaned as directed by the NPC.







SECTION VI- SPECIFICATIONS

PR NO /REF, NO .MG-A5M22-165/INFRA2022-AG5-052

TS - 1.11 Measurement and Payment

No separate measurement and payment will be made for the Contractor's Construction Facilities. The entire cost thereof shall be included in the various pay items in the Bill of Quantities.

TS - 2.0 CARE OF WATER DURING CONSTRUCTION

TS - 2.1 Scope

In accordance with the specifications contained in this section or otherwise directed, the Contractor shall construct and maintain all necessary temporary drainage ditches and other temporary protective works and he shall also furnish, install, maintain and operate necessary pumping equipment and other devices to protect construction operation free from water coming from any source, including rain.

TS - 2.2 Drainage and Dewatering

The Contractor shall be responsible for dewatering foundation areas so that work can be carried out on a suitably dry condition. The Contractor shall construct drainage ditches, holes, culverts, furnish, maintain and operate at his own expense all necessary pumps and other dewatering devices to keep all work area free from water.

After the work is completed and before it is accepted by the NPC, the Contractor shall remove all pumping equipment and shall remove, fill or plug all temporary drainage structures as directed, all at his expense.

TS - 2.3 Measurement and Payment

No separate measurement and payment will be made for the Care of Water during Construction operations. The cost of furnishing, constructing, maintaining, operating and removing of temporary drainage structure, pumping system and other dewatering devices necessary to keep construction operations free from water, shall be included in the various pay items in the Bill of Quantities for structures where such care of water is required.



PR NO./REF. NO. MG-A5M22-165/INFRA2022-AG5-052

TS-03CONSTRUCTION SAFETY AND HEALTH PROGRAM

TS - 3.1 Scope

This Section pertains to the environmental and safety provisions, requirements and conditions that shall govern during the execution of all civil works under this project.

TS - 3.2 General Conditions

The Contractor shall ensure compliance with the applicable environmental and safety regulations, as well as ECC conditions, during installation/construction of this project through the implementation of measures that include, but not limited to the following:

- Designate a Safety Officer and a Pollution Control Officer who shall respectively handle all safety and environmental concerns of the project.
- b. Prepare and submit Construction Safety Health Plan (CSHP)
- c. Properly manage debris and various waste generated during installation/construction, such as the following:
 - Dispose of demolition and construction debris in a designated or NPC approved disposal area (at the back of Central Warehouse near NGCP Switchyard Gate;
 - Stockpile (and cover if possible) or haul to the designated and/or pre developed dump sites (spoil disposal areas) that shall be provided with suitable drainage-equipped with sediments traps, stripped top soil, spoils from quarry/borrow sites and excavated materials;
 - Segregate solid wastes, such as empty cement sacks, scraps
 of tin or wood, used wires and other domestic, garbage, for
 recycling or storage in NPC-approved temporary storage
 areas and further disposal to LGU-designated disposal sites
 - Properly handle, store and dispose off, through DENRaccredited transporter/treater, hazardous wastes i.e. used oils, paints, thinner, Etc.
 - d. Limit construction activities that generate excessive noise to daytime works only to prevent nuisance to nearby residents during rest hours.
- e. As far as practicable, undertake site stripping, grading and excavation during dry weather.
- Construction/Installation shall be carried-out in a manner where landslides and erosions are minimized.





PR NO./REF, NO. MG-A5M22-165/INFRA2022-AG5-052

- g. Avoid unnecessary opening/clearing of areas outside construction sites or destruction of vegetable cover, especially cutting of existing trees; and to revegetate disturbed areas.
- Spray water, whenever and wherever necessary, to minimize dust generation.
- Provide PPE's and other safety provisions required by DOLE, for its project/site works.
- Submit proof of Tool Box meeting that was conducted in the course of the project. This will be attached on the contractor's progress billing.
- k. Composition of Occupational Safety and Health Team shall be displayed on the construction site or on the camp facilities that is visible to NPC inspectors and the construction workers. The size of the tarpaulin shall be 1.0m x 1.0m
- First aid kit (1 set) and ABC fire extinguishers (1set-20lbs) shall be present in the camp facilities and shall be turn-over to NPC after the completion of the project.

TS - 3.3 Measurement and Payment

Measurement and payment shall be made at the contract unit price or lot price as specified in the Bid Price Schedule. Payment shall include all cost in furnishing labor, materials, tools equipment and other incidentals necessary for the satisfactory implementation of this requirements.

TS-04 EXCAVATION WORKS

General

The work to be executed under this section shall include the furnishing of all, labor, tools and other facilities necessary for the satisfactory performance of all work necessary to complete the works specified in this specifications.

This Item shall include necessary diverting of live streams, bailing, pumping, draining, sheeting, bracing, and the necessary construction of cribs, and furnishing the materials therefore, and the subsequent removal of cribs and the placing of all necessary backfill.

It shall also include the furnishing and placing of approved foundation fill material to replaceunsuitablematerialencounteredbelowthefoundationelevationofstructures.

Construction Requirements

The Contractor shall notify the Engineer sufficiently in advance of the beginning of any excavation so that cross-section a elevations and





HYDROTOR USED OIL

SECTION VI- SPECIFICATIONS

PR NO./REF. NO.: MG-A5M22-165/INFRA2022-AG5-052

measurements may be taken on the undisturbed ground. The natural ground adjacenttothestructureshallnotbedisturbedwithoutpermissionoftheEngineer.

Trenches or foundation pits for structures or structure footings—shall be excavated to the lines and grades or elevations shown on the Plans or as staked by the Engineer. They shall be of sufficient size to permit the placing of structures or structure footings of the full width and length shown. The elevations—of—the—bottoms offootings,asshownonthePlans,shallbeconsideredasapproximateonlyand—the Engineer may order ,in writing, such changes in dimensions—or elevations of footings as may be deemed necessary ,to secure a satisfactory foundation.

Boulders, logs, and other objectionable materials encountered in excavation shall be removed.

After each excavation is completed, the Contractor shall notify the Engineer to that effect and no footing ,bed ding material or pipe culvert shall be placed until the Engineer has approved the depth of excavation and the character of the foundation material.

All rock or other hard foundation materials shallbecleanedallloosematerials, and cutto a firm surface, either level, stepped, or serrated as directed by the Engineer. All seams or crevices shall be cleaned and grouted. All loose and disintegrated rocks and thin strata shall be removed.

When the footing is to rest on material other than rock, excavation to final grade shall not be made until just before the footing is to be placed. When the foundation materialissoftormuckyorotherwiseunsuitable, as determined by the Engineer, the Contractor shall remove the unsuitable material and backfill with approved granular material. This foundation fill shall be placed and compacted in 150mm(6 inches) layers up to the foundation elevation.

Utilization of Excavated Materials

Allexcavatedmaterials, sofarassuitable, shall be utilized as backfillorembankmen to the surplus materials shall be disposed off in such manner as not to obstruct the stream or otherwise impair the efficiency or appearance of the structure. No excavated materials shall be deposited at anytime so as to endanger the partly finished structure.

MEASUREMENT AND PAYMENT

Measurement and payment shall be made at the contract unit price or lot price as specified in the Bid Price Schedule. Payment shall include all cost in furnishing labor, materials, tools equipments and other incidentals necessary for the satisfactory completion of the project.







PR NO./REF. NO.: MG-A5M22-165/INFRA2022-AG5-052

TS-05 BACKFILLING WORKS

General

The work to be executed under this section shall include the furnishing of all, labor, tools, equipment and other facilities necessary for the satisfactory performance of all work necessary to complete the works specified in this specifications.

Material Requirements

Embankments shall be constructed of suitable materials, in consonance with the following definitions:

SuitableMaterial-MaterialwhichisacceptableinaccordancewiththeContract and which can be compacted in the manner specified in this Item. It can be common material or rock.

Selected Borrow, for topping— soil of such gradation that all particles will pass a sievewith75mm(3inches)squareopeningsandnotmo rethan15masspercent willpassthe0.075mm(No.200) sieve, as determined byAASHTOT11. The materialshallhaveaplasticityindexofnotmorethan6as determinedbyASSHTO T90andaliquidlimitofnotmorethan30asdeterminedb yAASHTOT89.

Unsuitable Material-Material other than suitable materials such as:

- (a) Materialscontainingdetrimentalquantitiesoforganicmaterials, such asgrass, roots and sewerage.
- (b) Organic soils such as peat and muck.
- (c) Soils with liquid limit exceeding 80 and/or plasticity index exceeding 55.
- (d) Soils with a natural water content exceeding 100%.
- (e) Soilswithverylownaturaldensity, 800kg/m3orlower,
- (f) Soils that cannot be properly compacted as determined by the Engineer.

Construction Requirements





HYDROTOR USED OIL

PR NO /REF. NO. MG-A5M22-165/INFRA2022-AG5-052

SECTION VI- SPECIFICATIONS

General

Prior to backfilling works, all necessary clearing and grubbing in that area shall have been performed.

Backfills shall contain no muck, peat, sod, rootsor other deleterious matter. Rocks, broken concrete or other solid, bulky materials shall not be placed in embankment are as where pilingis to be placed or driven.

Where shown on the Plans or directed by the Engineer, the surface of the existing groundshallbecompactedtoadepthof150mm(6inches)and to the specified requirements of this Item.

Methods of Construction

Backfill of earth material shall be placed in horizontal lavers not exceeding200mm(8inches),loosemeasurement,andshallbecompactedasspeci fiedbeforethenextlayeris placed. However, thicker layer may be placed if vibratory roller with high compactive effort is used provided that density requirement is attained and as approved by the Engineer. Trial section to this effect must be conducted and approved by the Engineer Effective spreading equipment shall be used one a chlift to obtain uniform thickness as determined in the trial section prior to compaction. As the compaction of each layer progresses, continuous leveling and manipulating will be required to assure uniform density. Water shall be added or removed, if necessary, in order to obtain the required density. Removal of water shall be accomplished through aeration by plowing blading, discing, or other methods satisfactory to the Engineer.

Compaction

The Contractor shall compact the material placed in all embankment layers and the material scarified to the designated depth until a uniform density of notlessthan95masspercentofthemaximumdrydensitydeterminedbyAASHTOT

MEASUREMENT AND PAYMENT

Measurement and payment shall be made at the contract unit price or lot price as specified in the Bid Price Schedule. Payment shall include all cost in furnishing labor, materials, tools equipment and other incidentals necessary for the satisfactory completion of the project.

TS - 06CONCRETE WORKS

GENERAL

The work to be undertaken under this Section shall include all labor, materials, equipment, plant and other facilities and the satisfactory







HYDROTOR USED OIL

PR NO./REF. NO : MG-A5M22-165/INFRA2022-AG5-052

SECTION VI- SPECIFICATIONS

performance of all work necessary to complete all concrete work shown on the drawings and specified herein.

MATERIALS

a) Cement

Except as maybe otherwise provided in these specifications, cement shall conform to the "Specification for Portland Cement" (ASTM C 150 - Latest Revision) and shall be Type I

b) Concrete Aggregates

- Concrete aggregates shall be well graded, clean, hard particles of gravel or crushed rock conforming with the "Standard Specifications for Concrete Aggregates (ASTM C - 33 Latest Revision).
- 2.) The maximum size of the aggregates shall not be larger than one-fifth (1/5) of the narrowest dimension between form and not larger than three fourth (3/4) of the minimum clear spacing between individual reinforcing bars or bundles of bars, and in no case larger 5.1 cm (2 in) in diameter except that larger diameter may be allowed in massive concreting with written permission from the Engineer.

c) Water

Water used in mixing concrete shall be clean and free from injuring amounts of oils, acids, alkali, organic materials or other substances that may be deleterious to concrete or steel.

d) Reinforcing Steel

All reinforcing steel bars used shall be new and freefrom rust, oil, defects, greases or kinks. They shall conform to the latest edition of ASTM "SPECIFICATIONS FOR DEFORMED STEEL BARS FOR CONCRETE REINFORCEMENT" Grade 40 as shown or latest equivalent Philippine Bureau of Standard Specifications. Deformed Steel Bars shall have the following unit weights:

SIZE (mm)	Kg/m	SIZE (mm)	Kg/m
6	0.222	20	2.466
8	0.395	25	3.854
10	0.616	28	4.833
12	0.888	32	6.313
16	1.579	36	7.991

e) Admixture:







PR NO./REF, NO. MG-A5M22-165/INFRA2022-AG5-052

To increase concrete workability and to control the set of concrete, the engineer can request that an admixture maybe added subject to his approval and it shall be borne by the Contractor.

Water – reducing admixtures, retarding admixtures, accelerating admixtures, water-reducing and retarding admixtures, and water reducing and accelerating admixtures shall conform to "Specification for Chemical Admixtures for Concrete" (ASTM C494).

Other admixtures required for specific construction conditions and conforming to ASTM (C494) "Standard Specification for Chemical Admixtures for Concrete" maybe incorporated in separate concrete design mixes and submitted to the responsible engineer for approval prior to their use.

STORAGE OF MATERIALS

Cement and aggregates shall be stored in such a manneras to prevent deterioration or intrusion by foreign matter. Any material which has deteriorated or which has been damaged shall not be used for concrete. Steel shall be stored under cover or otherwise prevented from rusting.

CONTROLLED STRENGTHS OF CONCRETE

- 1.0.1 Concrete for structural elements shall develop a minimum 28-day compressive cylinder strength of 20.68 MPa (3,000 psi), unless otherwise specified in the plans.
- 1.0.2 Concrete for non-structural elements such as cradles, unreinforced encasements, thrust blocks, and partition walls shall develop a minimum 28-day compressive cylinder strength of 17.25 mega Pascal (2,500 psi), unless otherwise specified in the plans

CONCRETE PROPORTION AND CONSISTENCY

- a. The proportions of aggregate to cement for any concrete shall be such as to produce a mixture which will work readily into the corners and angles of the forms and around reinforcement with the method of placing employed on the work but without permitting the materials to segregate, or excess free water to collect on the surface. The combined aggregates shall be of such composition of sizes that when separated on the No. 4 standard sieve, the weight passing the sieve (fine aggregate) shall not be less than thirty percent (30%) of the total except that these proportions do not necessarily apply to lightweight aggregates.
- b. The methods of measuring concrete materials shall be such that proportions can be accurately controlled and easily checked at any time during the work. Measurement of materials for ready-mixed concrete







shall conform with the "Standard Specifications for Ready mixed Concrete" (ASTM C-94, Latest Revision) where applicable.

- c. Aggregates shall be measured out by weight and to within one percent (1%). Cement shall conform to 40 kg (88 lb.) per bag and this is to be verified from time to time. Water shall be measured by weight or volume to within one and one half (1-1/2 %).
- d. The water shall in no case exceed 21.24 liters, and 25.67 liters (5.62 and 6.79 US gallons) per bag of cement for all concrete with specified strength of fc respectively. Slumps shall be within the following limits:

Portion of Structure	Slump Millimeters	Inches	
Columns and end supported beams, girders	50-100	2-4	
Walls and thin Vertical sections	75-125	3-5	
Footings, slabs on Grade and cantileveredbeams and slabs	50-80	2-3	

Slumps shall be according to "Test of Slump for Portland Cement Concrete" (ASTM C-143).

e. Classification and Design Mixture. The mixtures forall classes of concrete shall be designed by the Contractor and approved by ICWS to obtain the compressive strength at the age of twenty eight (28) days as specified below.

Class Size of Maximum Dia. of Aggregate	Minimum Compressive Strength	Designated Size of aggregate
Y 1/2" (12.5mm)	3,000 psi	12.5mm to 4.75mm
AA 3/4" (19mm)	3,000 psi	19mm to 4.75mm
A 1-1/2" (37.5mm)	3,000 psi	37.5mm to 4,75mm
B 2" (50mm)	2,400 psi	50mm to 4.75mm
C 3" (75mm)	2,400 psi	75mm to 4.75mm

f. Cement Content. The minimum cement content per cubic meter of concrete for the different classes or gradation of aggregates shall be in accordance with the following:







PR NO./REF. NO. MG-A5M22-165/INFRA2022-AG5-052

Class and Gradation of Aggregates	Minimum Cement Content
Y with 1/2"	400 kgs/cu.m
AA with 3/4"	400 kgs/cu.m
A with 1-1/2"	360 kgs/cu.m
B with 2"	600 kgs/cu.m
C with 3"	270 kgs/cu.m
Z with 3"	340 kgs/cu.m

g. Job mix adjustments on water content shall be allowed only with Engineer's permission and provided that cement is also added to maintain the original water cement ratio of the design mix.

EXCLUSION OF WATER

No concrete shall be placed in any structure until all water entering the space to be filled with concrete has been properly cut off or has been diverted by pipes, or other means, and carried out of the forms, clear of the work. No concrete shall be deposited under water without the explicit permission of the Engineer, and then only in strict accordance with his directions; nor shall the Contractor, without explicit permission allow still water to rise on any concrete until the concrete has attained its initial set. Water shall not be permitted to flow over the surface of any concrete in such manner and at such velocity as will injure the surface finish of the concrete. Pumping or other necessary dewatering operations for removing ground water, if required, will be subject to the approval of the Engineer.

MIXING CONCRETE

No hand mixing shall be allowed, except in case ofemergency such as mixer breakdown during pouring operations and shall stop at the first allowed construction joints. All concrete shall be machine mixed for at least 1 minutes after all materials including water are in the mixing drum.

The mixer shall be of approved size and type which will insure a uniform distribution of material throughout the mass, it shall be equipped with a device for accurately measuring and controlling amount of water in each batch.

Placing of material in mixer shall be done in such a way that first batch of concrete materials placed in the mixer shall contain sufficient excess of



PR NO /REF. NO.: MG-A5M22-165/INFRA2022-AG5-052

cement, sand and water to coat the inside of the drum without reducing the cement content of the mix to be discharged.

Retempering, i.e., remixing with the addition of water to concrete that has been partially hardened shall not be permitted.

PREPARATION OF SURFACES FOR CONCRETING

Earth surfaces shall be thoroughly wetted by sprinkling prior to the placing of any concrete, and these surfaces shall be kept moist by frequent sprinkling up to the time of placing concrete thereon. The surface shall be free from standing water, mud, and debris at the time of placing concrete.

Concrete surfaces upon or against which concrete is to be placed, where the placement of the old concrete has been stopped or interrupted so that, in the opinion of the Engineer, the new concrete cannot be incorporated integrally with that previously placed, are defined as construction joints. The surfaces of horizontal joints shall be leveled with a wooden float to provide a reasonably smooth surface. A surface consisting largely of coarse aggregate shall be avoided. Except where the drawings call for joint surfaces to be painted, the joint surfaces shall be cleaned of all laitance, loose or defective concrete, and foreign material. Such cleaning shall be accompanied by sandblasting followed by thorough washing. All pools of water shall be removed from the surface of construction joints before the new concrete is placed. After the surfaces have been prepared to the satisfaction of the Engineer, all approximately horizontal construction joints shall be covered with a layer of mortar approximately 25mm (1") thick. The mortar shall have the same proportion of cement and sand as the regular concrete mixture, unless otherwise directed by the Engineer. The water-cement ratio of the mortar in place shall not exceed that of the concrete to be placed upon it, and the consistency of the mortar shall be suitable for placing and working in a manner hereinafter specified. The mortar shall be spread uniformly and shall be worked thoroughly into all irregularities of the surface, and wire brooms shall be used where possible to scrub the mortar into the surface. Concrete shall be placed immediately upon the fresh mortar.

When placing of concrete is to be interrupted long enough for the concrete to take a set, the working face shall be given a shape by the use of forms or other means that will secure proper union with subsequent work, provided that construction joints shall be made only where approved by the Engineer.

PLACING OF CONCRETE

Concrete which upon or before placing is found not to conform with the requirements specified herein shall be rejected and immediately removed from the work. Concrete which is not placed in accordance with these specifications, or which is of inferior quality, as determined by the engineer, shall be removed and replaced by and at the expense of the Contractor. No concrete shall be placed except in a present of duly authorized representative of the Engineer. Concrete shall not be placed when unsuitable heat or wind will prevent proper placement and curing, as determined by the Engineer.



PR NO./REF. NO.: MG-A5M22-165/INFRA2022-AG5-052

prior to placing any concrete, the Contractor shall give the Engineer twenty four (24) hours written notice.

Concrete shall be deposited in its final position without segregation, rehandling, or flowing. Placing shall be done preferably with buggies, buckets, or wheel borrows. No chutes will be allowed except to transfer concrete from hoppers to buggies, wheel borrows, or buckets in which case, they shall not exceed six (6) meters (20') in aggregate length.

Placing of concrete with a free drop or fall more than 1.20m (4') shall not be allowed, except when approved by the Engineer and when approved sheet metal conduits, pipes or "elephant trunks" are employed. When employed, these conveyors shall be kept full or concrete and the ends kept buried in the newly placed concrete as pouring progresses.

Concrete in forms shall be deposited in uniform horizontal layers not deeper than 450mm (18") and care shall be taken to avoid inclined layers or inclined construction joints except where such care required for sloping members. Each layer shall be placed while the previous layer is still soft. The rate of placing concrete in forms shall not exceed 1.5 meters (5") of vertical rise per hour.

TAMPING AND VIBRATING

As concrete is placed in the forms or in excavations, it shall be thoroughly settled and compacted throughout the entire depth of the layer which is being consolidated, into a dense, homogeneous mass, filling all corners and angles, thoroughly embedding the reinforcement, eliminating rock pockets, and bringing only a slight excess of water to the exposed surface of concrete during placement.

Care shall be used in placing concrete around waterstops. The concrete shall be carefully worked by rodding and vibrating to make sure that all air and rock pockets have been eliminated. Where flat-strip type waterstops are used, the concrete shall be worked under the waterstops are used, the concrete shall be worked under the waterstops by hand making sure that all air and rock pockets have been eliminated.

Concrete in wall shall be internally vibrated and at the same time rammed, stirred, or worked with suitable appliances, tamping bars, shovels, or forked tools until it completely fills the forms or excavations and closes snugly against all surfaces. Subsequent layers previously placed have been worked thoroughly as specified. Except in special cases where their use is deemed impracticable by the Engineer, the Contractor shall use internally vibrated, high speed power vibrators not less than 8000 rpm of an approved immersion type in sufficient numbers, with standby units as required, to accomplish the results herein specified within fifteen (15) minutes after concrete of the prescribed consistency is placed in the forms. The vibrating head shall be kept from contact with the surfaces of the forms. Care shall be taken not to vibrate concrete excessively or to work it in any manner that causes segregation of its face.





PR NO /REF. NO. MG-A5M22-165/INFRA2022-AG5-052

CARE AND REPAIR OF CONCRETE

The Contractor shall protect all concrete against injury or damage from excessive heat, lack of moisture, over stress, or any other cause until final acceptance by the Owner. Particular care shall be taken to the drying of concrete and to avoid roughening or otherwise damaging the surface. Any concrete found to be damaged or which may have been originally defective at any time prior to the final acceptance of the complete work, or which departs from the established line or grade, or which for any other reason does not conform with the specifications shall be satisfactorily repaired or removed and replaced with acceptable concrete at the Contractor's expense.

FINISH OF CONCRETE SURFACE


All finished or formed surfaces shall conform accurately with the shape, alignment, grades and sections as indicated on the plans or as prescribed by the Engineer. Surfaces shall be free from fins, bulges, ridges, offsets, honeycombing, or roughness of any kind, and shall present a finished, smooth, continuous hard surface.

Except as otherwise provided herein, unformed top surfaces of concrete shall be brought to uniform surfaces and worked with suitable tools to a reasonably smooth wood float finish. Excessive floating of surfaces while the concrete is plastic will not be permitted. All surfaces shall be placed monothically with the base slab. Dusting of dry cement and sand on the concrete surface to absorb excess moisture will not be permitted. Floor slabs and exposed tops of walls and curbs shall be given a steel trowel finish. At the Contractor's option, the above mentioned floor slabs may be finished with a power float after screeding. Subsequent to the aforementioned finish, all sloping surfaces of floor slabs shall be lightly boomed to provide a skid resistant surface

TREATMENT OF SURFACE DEFECTS

As soon as forms are removed, all exposed surfaces shall be carefully examined and any irregularities shall be immediately rubbed or ground in a satisfactory manner in order to secure a smooth, uniform, and continuous surface. Plastering or coating of surfaces to be smoothed will not be permitted. No repairs shall bemade until after inspection by the Engineer, and then only in strict accordance with his directions. Concrete containing voids, holes, honeycombing, similar depression defects shall be completely removed and replaced; provided that where required or approved by the Engineer, defects shall be repaired with gunite or with cement mortar placed by an approved compressed air mortar gun. In no case will extensive patching of honey combed concrete be permitted. All repairs and replacements herein specified shall be promptly executed by the Contractor at his own expense.





HYDROTOR USED OIL

PR NO./REF. NO. MG-A5M22-165/INFRA2022-AG5-052

SECTION VI- SPECIFICATIONS

DEPOSITING CONCRETE

Depositing:

Depositing shall be done without segregation, remanding or flowing of concrete. It shall be done with the use of buggies, buckets or wheelbarrows. Use of chutes will not be allowed except to transfer concrete from hoppers to buggies, wheelbarrows or buckets in which case shall not exceed 20 feet in aggregate length placing of concrete with a free drop of fall of more than 5 feet are not allowed. Conveyors when used shall be kept full of concrete and ends shall be kept buried in the newly placed concrete as pouring progresses.

Vibrations:

No placing of concrete will be allowed without vibrators. Segregation due to over vibration shall be avoided.

Construction Joints:

If possible concreting shall be done continuous until section is complete. When stoppage of concrete operations occur, construction joints shall be placed either horizontally or vertically as indicated by the Engineer and provided with shear keys or dowels to develop bond. Construction joints shall be per plan or shall be approved or as directed by the Engineer.

MEASUREMENT AND PAYMENTS.

"Class A "concrete shall be measuredby the cubic meter (cu.m.) of concrete completed in place and accepted.

Measurement will be of the actual number of cubic meter within theneat lines of the structure as shown in the plans or revised by authority of the Engineer. The volume of concrete measured as determined above shall be paid for at the contract unit price per cubic meter (cu.m.) which price and payment shall be full compensation mixing, placing, finishing and curing the concrete and all labor, equipment, tools and incidentals necessary to complete the item and accepted.

Payments for the reinforcement placed shall be included in the contract unit price per cubic meter (cu.m.) of concrete which price and payment shall be the full compensation of all labor, equipment, tools and incidentals necessary to complete the item and accepted.

Concrete forms placed shall be included in the contract unit price per cubic meter (cu.m.) of concrete which price and payment shall be the full compensation of all labor, equipment, tools and incidentals necessary to complete the item and accepted.

TS - 07CONCRETE MASONRY





PR NO./REF. NO. MG-A5M22-165/INFRA2022-AG5-052

General

Concrete masonry construction shall include the furnishing of all labor, material, and equipment, and performing all operations necessary to execute all concrete masonry construction, as specified.

Contractor shall make all preparations and do all work necessary to receive and adjoin other work.

Contractor shall give the work his personal supervision and shall keep a competent foreman on the job at all times when he is not there himself.

Contractor shall specify the position of all dowels required for masonry on otherconstruction,

including foundations. Contractors hall arrange for the necessary storages pace for construction materials at the jobsite.

ContractorshallcallforallinspectionsrequiredinthecourseofhisworkbyOwner.

Materials

Concrete Hollow Blocks

All property wall shall be 150mm thick x 200mm x 400mm non-bearing concrete hollow blocks, otherwise, use 100mm thick x 200mm x 400mm non-bearing concrete hollow blocks

Mortar / Grout

Mortar/grout shall be a mixture of 1 part cement and 3 parts fine sand

Reinforcing Steel

Reinforcing steel shall be 10mm diameter, Grade 40, spaced at 600mm oncenter along horizontal and vertical of the walls. Reinforcement shall be secure with a Ga. 16 tie wire.

Masonry Construction

Blocksshallbecutaccuratelytofitallplumbingducts,openings,electricalwork,andall voidsslushedfull.Wherewallsaretoreceiveplaster,thejointsshouldbestruckflush. Wherecertainjointsaretobeconcealedunderpaint,thesejointsshallbefilledflushan dthensackedtoproduceadensesurfacewithoutsheen.

Vertical head joints shall be buttered well for a thickness equal to the face shell of the block and these joints shall be shoved tightly so that the mortar bonds well to both blocks. Joints shall be solidly filled from the face of the block to the depth of the face shell.

Grouting

Reinforcingsteelshallbeinplaceandinspectedbeforegroutingstarts. Verticalcellsto be filled with mortar shall have vertical alignment to maintain a continuous





HYDROTOR USED OIL

PR NO./REF. NO. MG-A5M22-165/JNFRA2022-AG5-052

SECTION VI- SPECIFICATIONS

unobstructed cell area. Cells containing reinforcement shall be solidly filled with grout.

Plastering

Mixture

Mortar mixture for brown coat shall be freshly prepared and uniformly mixed in the proportion by volume of one part Portland Cement, three (3) parts sand.

 a) Finish coat shall be pure Portland Cement properly graded. Hydraulic Cement and mixed with water to approved consistency and plasticity.

Surface Preparation

- After removals of formworks reinforce concrete surfaces shall be roughened to improve adhesion of cement plaster.
- b) Surfaces to receive cement plaster shall be cleaned of all projections, dust, loose particles, grease and bond breakers. Before any application of brown coat is commenced all surfaces that are to be plastered shall be wetted thoroughly with clean water to produce a uniformly moist condition.

Application

- a) Brown coat mortar mix shall be applied with sufficient pressure starting from the lower portion of the surface to fill the grooved and to prevent air pockets in the reinforced concrete/masonry work and avoid mortar mix drooping. The brown coat shall be lightly broomed/ or scratch before surface had properly set and allowed to cure.
- b) Finish coat shall not be applied until after the brown coat has seasoned for seven days and corrective measures had been done by the Contractor on surfaces that are defective. Just before the application of the finish coat, the brown coat surface shall be evenly moistened with potable water. Finish coat shall be floated first to a fue and even surface, then troweled in a manner that will force the mixture to penetrate into the brown coat. Surfaces applied with finish coat shall then be smooth with paper in a circular motion to remove trowel marks, checks and blemishes. All cement plaster finish shall be 10 mm thick minimum on vertical concrete and/or masonry walls.

Workmanship

Cement plaster finish shall be true to details and plumbed. Finish surface shall have no visible junction marks where one (1) Day's work adjoins the







PR NO./REF. NO MG-A5M22-165/INFRA2022-AG5-052

other. Where directed by the NPC or as shown on the Plans vertical and horizontal groove joints shall be 25 mm wide and 10 mm deep.

MEASUREMENT AND PAYMENT

Measurement and payment shall be made at the contract unit price or lot price as specified in the Bid Price Schedule. Payment shall include all cost in furnishing labor, materials, tools equipments and other incidentals necessary for the satisfactory completion of the project.

TS - 08 ROOF FRAMING (WELDING AND STEEL WORKS)

General

The work to be executed under this section shall include the furnishing of all, labor, tools, equipment and other facilities necessary for the satisfactory performance of all work necessary to complete all demolition and disposal works.

Work Included

a) The work included under this section shall include the furnishing, fabrication, erection and/or installation of all steel roof framing, steel girts and other work indicated in the Plans and Specifications.

Materials

- a) All G. I. pipes shall be schedule 40 unless otherwise noted in the Plans.
- b) Rectangular tube and C-Purlins shall have a 1.00mm thickness
- c) Angle barsand flat bars shall be have a thickness of 3/16"
- d) All arc-welding electrodes shall conform to the requirements of the American Welding Society "SPECIFICATIONS FOR IRON AND STEEL ARC-WELDING ELECTRODES" latest edition

Connections

 Shop connections shall be welded unless otherwise indicated in the Plans. All connections shall develop full strength of members.

Workmanship and Fabrication

- a) Workmanship and fabrication shall be in accordance with AISC "Specification for Fabrication and Erection of Structural steel for Buildings" and with the following outline.
- Bearing surfaces shall be planed to true beds. Abutting surfaces shall be closely fitted
- c) All columns and bearing stiffeners shall be milled to give full bearing over the cross section. It shall not be necessary to plane bottom surfaces of plate on grout beds.
- d) Assembled parts shall be brought into close contact, and drift pin shall be used only for bringing members into position, not to enlarge or distort holes.





PR NO:/REF. NO MG-A5M22-165/INFRA2022-AG5-052

Welding

a) Welding in shop and field shall be done by qualified welders. Equipment shall be of the type, which produce proper current so that operator may produce satisfactory welds. The welding machine shall be of 300 amperes, 200 -240 volts capacity.

b) Unless otherwise shown on the Plans, the following low hydrogen electrodes shall be used and shall be suitable for positions and other conditions of intended use in accordance with the instruction with each container.

Welding	Electrode	Submerged Arc Process
A-7 to A-7	E - 60 Series	Grade SAW-2
A-7 to A-36	E - 70 Series	Grade SAW-2
A-36 to A-36	E - 70 Series	Grade SAW-2

- c) The technique of welding employed, the appearance and quality of welds made, and the methods of correcting defective work shall conform to the American Welding society code for arc welding. Surfaces to be welded shall be free from loose scale, rust, grease, paint and other foreign material except that mill scale, which withstands vigorous wire brushing, may remain
- finish members shall be true to line and free from twists, bends and open joints.

Measurement and Payment

Measurement and payment shall be made at the contract unit price or lot price of the various applicable items specified in the Bid Price Schedule. Payment shall include all cost in furnishing labor, materials, equipments and other incidentals necessary for the satisfactory completion of the project.

TS - 09 ROOFING WORKS AND SIDING SHEETS

General

The contractor shall furnish all labor, materials and operations including tools, other implements and accessories for the complete installation of roofing sheets wherever indicated in the drawings.





PR NO./REF. NO. MG-A5M22-165/INFRA2022-AG5-052

Installation shall be performed by skilled workmen in accordance with the construction and shop drawings and the manufacturer's standard.

Shop drawings and manufacturer's catalogue showing product standards and technical data will be provided by the Contractor to the NPC representative for approval.

Materials

Material for roofing shall be weather and chemical resistant. It shall be corrugated aluminum-zinc-silicon alloy coated metal sheet. Base metal shall be determined as specified in the drawing that shall range from 0.4 to 0.60mm thick. Branded sheets such as flat barge caps, flashings, ridge rolls, capping and mouldings that serve as its accessory components shall have the same composition with the roofing and sidings of which minimum thickness base metal shall be 0.5mm. Gutters likewise shall have the same material composition with base metal thickness of 0.50mm unless otherwise specified in the drawing commonly as stainless.

Workmanship

Roofing and siding sheets shall be securely fastened on purlins and channels by hook or stove bolts or self-drilling screws or as required, Fasteners shall have a maximum distance of 0.30m O.C. along purlins.

Special care shall be given to the joints, lapping, bolting and setting of closers.

Measurement and Payment

Measurement and payment for Roofing Works and Siding Sheets will be based on the projected area inspected and accepted by the NPC Representative. No measurement & payment will be made on hidden areas covered by side & end overlaps, the cost for these being included in the projected area.

Payment will be made at the corresponding unit price per square meter including ridge roll, flashing, capping for pertinent items in the Bill of Quantities

TS-10 ELECTRICAL WORKS

Work Included

The work included under this section shall include the furnishing, fabrication, erection and/or installation of electrical system and other steel work indicated in the Plans and Specifications.

Standard of Materials

All materials to be used in the work shall be new, of high quality, free from all defects and of proven acceptability from the purpose of intended. Unless otherwise specified, materials shall conform to the latest applicable standard issued by the following authorities:



PR NO./REF. NO. MG-A5M22-165/INFRA2022-AG5-052

- a) American National Standards Institute (ANSI)
- b) Institute of Electrical and Electronic Engineers (IEEE)
- c) Underwriter's Laboratory (UL)
- d) National Electrical Manufacturers Association (NEMA)
- e) National Electrical Code (NEC)
- f) Philippine Electrical Code (PEC)

Other recognized national standards maybe accepted if, in the opinion of NPC representatives, such will guarantee a quality not inferior to that guaranteed by the above standards.

In case of conflicting requirements between authorities cited above and those specified, such disagreement shall be resolved by representative of which his decision shall be final.

Lighting System

The lighting system covered by this specification includes associated conduits and cables, lighting fixtures, fittings, etc.

The device/materials furnished shall be in accordance with, but not limited to, the latest issues of the Applicable Codes and Standards, including all addenda, in effect at time of purchase order unless otherwise stated in this Specification.

All materials and parts which are not specifically mentioned herein but are necessary for the proper installation and safe operation of the lighting system shall be identified by the Contractor and shall be furnished at no additional cost to NPC.

Lighting Fixtures and Accessories

Street Lighting Fixtures

All lighting fixtures when installed shall be free of leaks, warps, dents and other irregularities.

All lighting fixtures, samples and catalogues shall be submitted for NPC's review and approval prior to the order. No lighting fixtures shall be installed without the approval of NPC.

Lighting fixtures shall be wired with approved wire, 75°C insulation. Each fixture shall be wired to a single point with an adequate slack for proper connection. All lighting fixture shall be protected from damage during installation. Any broken lighting fixtures, receptacle, stem and the like shall be replaced with new parts, at no cost to NPC.

Cables / Wires

Cable shall be stranded annealed copper conductor suitable for continuous temperature of 90°C when used in wet or dry location and 90°C when exposed to oil or coolant. The minimum size of conductor to be used shall be 5.5mm2





PR NO./REF. NO. MG-A5M22-165/INFRA2022-AG5-052

The cables shall be designed for trouble free service for the highest system voltage. All cables and their accessories to be supplied shall have insulation levels able to withstand any voltage surges which are normally expected to occur in the power system in which are normally expected to occur in the power system in which the cable is to be employed, due to switching operations, sudden load variation, faults, etc.

The cables and accessories shall be constructed to fulfill the requirements when operating with full load or any load factor and is suitable for use in ducts, trays and or direct burial in ground.

Cables Installation

Cable pulled through conduit shall be supported in an approved manner so as to avoid damaged to the insulation. Grease or oily substances shall not be used to facilitate the passage of the conductor in conduits.

The pull shall be applied to cables only by means of approved grips and the end portion of the cable which has been marked or deformed by the grip shall be cut-off by the Contractor.

All cable runs shall be continuous and all termination shall be at the terminal boards, equipment, etc. No splices are allowed in conduit or cable tray.

Prior to installation of cables, conduits shall be thoroughly cleaned to prevent damage to cables during installation. After cables have been installed, cables shall be tested for continuity and insulation resistance and shall be tagged with respective cable number

Conduits

All conduits, boxes and fittings required for the power and control conductors including necessary hardware and accessories such as screws, bolts, concrete inserts, clamps, locknuts, couplings shall be furnished by the Contractor. The required quantities shall be furnished in accordance with the installation requirements.

During installation, due precaution shall be taken to protect the conduit and threads from mechanical injury. The ends of the conduit shall be sealed in an approved manner, Conduit runs shall be sealed by the use of caps and discs or plugs. The seals shall be maintained, except during inspection and tests, until the conductor is pulled in. Conduit shall be check to be free from obstructions by pulling a wooden mandrel of appropriate size through the conduit.

Conduits installed outdoors running underground shall be buried to a minimum of 0.457 m.

Measurement and Payment

Measurement and payment shall be made at the contract unit price or lot price of the various applicable items specified in the Bid Price Schedule. Payment shall include all cost in furnishing labor, materials, equipment and other incidentals necessary for the satisfactory completion of the project.

TS-11 CEILING WORKS



PR NO./REF. NO. MG-A5M22-165/INFRA2022-AG5-052

General

The work to be executed under this section shall include the furnishing of all, labor, tools and ladders, scaffolding and other facilities necessary for the satisfactory performance of all work necessary to complete the works specified in this specifications.

Material

Materials to be used shall be the following but not limited to:

- Double Furring
- 2. Wall Angle
- 3. 1/4" thick Fiber Cement Board
- 4. Blind Rivets

Workmanship

All work shall be done by skilled workers in a workmanlike manner.

Wall angles shall be firmly secured at the walls of the building though nails. All double furring shall be installed firmly and aligned. Nylon or string connected wall to wall shall be used so that correct level of furring will be attained. Fiber cement board shall be installed and secured on the furring through rivets or screws.

MEASUREMENT AND PAYMENT

Measurement and payment shall be made at the contract unit price or lot price as specified in the Bid Price Schedule. Payment shall include all cost in furnishing labor, materials, tools equipment and other incidentals necessary for the satisfactory completion of the project.


TS -12 PAINTING, VARNISHING AND OTHER RELATED WORKS

General

This Item shall consist of furnishing all paint materials, varnish and other related products, labor, tools, equipment and plant required in undertaking the proper application of painting, varnishing and related works indicated on the Plans and in accordance with this Specification.

Material Requirements

- 1. Top Coat, Liquid Tile or approved equivalent
- 2. Primer, Liquid Tile or approved equivalent
- 3. Tile Cast
- 4. Liquid Tile Reducer
- Brush and Roller



PR NO /REF. NO. MG-A5M22-165/INFRA2022-AG5-052

Paint Materials

All types of paint material, varnish and other related product shall be subject to random inspection by NPC Inspector or GSFM (Use the following approved and tested brand name: Boysen, Davies, Dutch Boy, Fuller 0 Brien, or any approved equal).

Tinting Colors

Tinting colors shall be first grade quality, pigment ground in alkyd resin that disperses and mixes easily with paint to produce the color desired. Use the same brand of paint and tinting color to effect good paint body.

Concrete Neutralizer

Concrete neutralizer shall be first grade quality concentrate diluted with clean water and applied as surface conditioner of new interior and exterior walls thus improving paint adhesion and durability.

Silicon Water Repellant

Silicon water repellant shall be transparent water shield especially formulated to repel rain and moisture on exterior masonry surfaces.

Patching Compound

Patching compound shall be fine powder type material like calcimine that can be mixed into putty consistency, with oil base primers and paints or premix glazing putty, tile cast to fill minor surface dents and imperfections whichever is applicable.

Varnish

Varnish shall be a homogeneous solution of resin, drying oil, drier and solvent. It shall be extremely durable clear coating, highly resistant to wear and tear without cracking, peeling, whitening, spotting, etc. with minimum loss of gloss for a maximum period of time.


Lacquer

Lacquer shall be any type of organic coating that dries rapidly and solely by evaporation of the solvent. Typical solvent are acetates, alcohols and ketones. Although lacquers were generally based on nitrocellulose, manufacturers currently use, vinyl resins, plasticizers and reacted drying oils to improve adhesion and elasticity.

Sanding Sealer

Sanding sealer shall be quick drying lacquer, formulated to provide quick dry, good holdout of succeeding coats, and containing sanding agents such as zinc stearate to allow dry sanding of sealer.

Construction Requirements



PR NO./REF. NO. MG-A5M22-165/INFRA2022-AG5-052

The Contractor prior to commencement of the painting, varnishing and related work shall examine the surfaces to be applied in order not to jeopardize the quality and appearances of the painting varnishing and related works.

Surface Preparation

All surfaces shall be in proper condition to receive the finish. Woodworks shall be hand-sanded smooth and dusted clean. All knotholes pitch pockets or sappy portions shall be sealed with natural wood filler. Nail holes, cracks or defects shall be carefully puttied after the first coat, matching the color of paint.

Interior woodworks shall be sandpapered between coats. Cracks, holes of imperfections in plaster shall be filled with patching compound and smoothed off to match adjoining surfaces.

Concrete and masonry surfaces shall be coated with concrete neutralizer and allowed to dry before any painting primer coat is applied. When surface is dried apply first coating. Hairline cracks and unevenness shall be patched and sealed with approved putty or patching compound.

After all defects are corrected apply the finish coats as specified on the Plans (color scheme approved).

Metal shall be clean, dry and free from mill scale and rust. Remove all grease and oil from surfaces. Wash unprimed galvanized metal with etching solution and allow it to dry. Where required to prime coat surface with Red Lead Primer same shall be approved by the NPC Engineer.

In addition the Contractor shall undertake the following:

- Voids, cracks, nick etc. will be repaired with proper patching material and finished flushed with surrounding surfaces.
- Marred or damaged shop coats on metal shall be spot primed with appropriate metal primer.
- Painting and varnishing works shall not be commenced when it is too hot or cold.
- 4. Allow appropriate ventilation during application and drying period.
- All hardware will be fitted and removed or protected prior to painting and varnishing works.


Application

Paints when applied by brush shall become non-fluid, thick enough to lay down as adequate film of wet paint. Brush marks shall flaw out after application of paint.

Paints made for application by roller must be similar to brushing paint. It must be nonstick when thinned to spraying viscosity so that it will break up easily into droplets.

Paint is atomized by high pressure pumping rather than broken up by the large volume of air mixed with it. These procedures change the required properties of the paint.





PR NO./REF, NO. MG-A5M22-165/INFRA2022-AG5-052

Mixing and Thinning

At the time of application paint shall show no sign of deterioration. Paint shall be thoroughly stirred, strained and kept at a uniform consistency during application. Paints of different manufacture shall not be mixed together. When thinning is necessary, this may be done immediately prior to application in accordance with the manufacturer's directions, but not in excess of 1 pint of suitable thinner per gallon of the paint.

Storage

All material to be used under this Item shall be stored in a single place to be designated by the Engineer and such place shall be kept neat and clean at all time. Necessary precaution to avoid fire must be observed by removing oily rags, waste, etc. at the end of daily work.

Cleaning

All cloths and cotton waste which constitute fire hazards shall be placed in metal containers or destroyed at the end of daily works. Upon completion of the work, all staging, scaffolding and paint containers shall be removed. Paint drips, oil, or stains on adjacent surfaces shall be removed and the entire job left clean and acceptable to the Engineer.

Workmanship in General

- a) All paints shall be evenly applied. Coats shall be of proper consistency and well brushed out so as to show a minimum of brush marks.
- b) All coats shall be thoroughly dry before the succeeding coat is applied.
- c) Where surfaces are not fully covered or cannot be satisfactorily finished in the number of coats specified such preparatory coats and subsequent coats as may be required shall be applied to attain the desired evenness of surface without extra cost to the owner.
- d) Where surface is not in proper condition to receive the coat the Engineer shall be notified immediately. Work on the questioned portion(s) shall not start until clearance be proceed is ordered by the NPC Engineer.
- e) Hardware, lighting fixture and other similar items shall be removed or 'protected during the painting varnishing and related work operations and re-installed after completion of the work.

MEASUREMENT AND PAYMENT

Painting and/or varnishing shall be measured in square meter (sq.m.) of painting completed in place and accepted. Measurement will be of the actual number of square meter within the neatlines of the structure as shown in the plans or revised by authority of the NPC Engineer. The area of painting measured as determined above shall be paid for at the contract unit price per square meter (sq.m.) which price and payment shall be full compensation of all labor, equipment, tools and incidentals necessary to complete the item and accepted.


TS-13 CLEARING AND DEMOBILIZATION



PR NO./REF. NO. MG-A5M22-165/INFRA2022-AG5-052

Before moving out, the contractor shall restore the orderly state of worksite by clearing all temporary structures. Remove all excess/waste materials and store in designated areas.

Before the Contractor will demobilize its construction equipment/ tools, materials and crew, he shall secure approval from NPC security office for the release of the contractor's equipment and to surrender the workers Identification (I.D) cards. A joint inspection with the NPC inspector and Contractor will be conducted to make sure that all his accomplishment / work that needs remedial attention or correction shall be done prior to the issuance of the Certificate of Completion. The Certificate of Completion will serve as basis for the processing of payments.



PRINO//REF NO. MG-A5M22-185/INFRA2022-AG5-052

Section VII. Drawings

Sheet No. 1/5-VICINITY MAP/LOCATION PLAN / PERSPECTIVE


Sheet No. 2/5- PEDESTAL, CYLINDRICAL TANK, ANCHOR BOLT DETAILS

Sheet No. 3/5-FOUNDATION PLAN, SECONDARY CONTAINMENT PLAN, OIL&STORM WATER TRAP SECTION DETAILS

Sheet No. 4/5-FRONT, REAR ELEVATION & SECTION

Sheet No. 5/5-ROOF DETAILS, ROOF SEQUENCE






PERSPECTIVE


Plant Both and Age 4.8 To PC	N. D. HIGRA	一人工		Value panis	CAL MARKET) AGOS STIET	NATIONAL POWER CORPORATION Mindanao Generation
MECH	EURO	CMIL/ARCHT	REVIEWED	DRAWN	DESIGNED		LOCATION	PROJECT
		-	PRINCIP			-γ8		
			PRINCIPAL ENGR. / ARCHIT			CHED		TAI
			ROHT			DATE		SUS 4 II
						PARTICULARS		AGUS 4 INST. OF CYLINDRICAL TANK FOR HYDROTOR USED OIL

SHEET NO.

OWG


Ü








NOTE:

The SECONDARY CONTAINMENT Must have a sufficient capacity to contain not less than its for the tank's volume.











NATIONAL POWER CORPORATION Mindanao Generation	PROJECTS	AGUS 4 INST. OF CYLINDRICAL TANK FOR HYDROTOR USED OIL				
AGUS 5 HEP	LOCATION					
to takent		BY	CHKD	DATE	PARTICULARS.	A /
LG, NAMOSO SUPPLITTED C.V.L. ALAMAG	DESIGNED					
REPAIRED SUBMITTED SUBMITTED Plant C/M Manager, Agus 4 HEP	DRAWN					
MATTER	REVIEWED	PRINCI	PALENGR /	ARCH'T.		/ 3
A Thirty of the same of the sa	CIVIL/ARCHIT					
ECOMMENDED N.T. BENIGRA APPOVED EATVELOSOUR	ELEC.	1				
ECOMMENDED N.T. PENIGRA APROVED E.A. VELOSO-IR. Plink Maring Puly 4 1 5 HEPC VEC VICE Prosper fundament Generation	MECH.					DWG





PRING /REF NO MG-A5M22-165/INFRA2022-AG5-052

Section VIII. Bill of Quantities

NAME OF PROJECT . INSTALLATION OF CYLINDRICAL TANK FOR HYDROTOR USED OIL PRIND/REF NO. MG-A5M22-165/INFRA2022-AG5-052

Name of Project

INSTALLATION OF (

PR#

MG-A5M22-165

SECTION VIII - BILL OF QUANTITIES

BILL OF QUANTITIES

<u> </u>			BILL OF	QUANTITIES
Item No.	Description of Work or Materials	Estimated Quantity	Unit	Unit Price in Pesos (Words and Figures)
1	PURCHASE OF FABRICATED CYLINDRICAL TANK (14,000 L)	1	lot	
2	SITE WORKS	1	lot	
3	LAY-OUT AND STAKING	1	lot	
4	EXCAVATION	4.65	cu.m	

PR NOUREF, NO. MC-A5M22-185/INFRA2022-AG5-052

5	EMBANKMENT WORKS	5	cu.m	
6	REINFORCED CONCRETE WORKS	.3.22	cu.m.	
7	MASONRY WORKS	12	sq.m.	
8	STEEL STRUCTURE	1	lot:	
9	ROOFING WORKS	1	lot	

NAME OF PROJECT INSTALLATION OF CYLINDRICAL TANK FOR HYDROTOR USED OIL PRING /REF NO MG-A5M22-165/INFRA2022-AG5-052

	Name of Firm			Name and Signature of Authorized Represe	ntative
12	PAINTING WORKS	1	lot		
11	ELECTRICAL WORKS	1	lot		
10	MECHANICAL WORKS	1	lot		

BID DOCUMENTS

SECTION IX- CHECKLIST OF TECHNICAL & FINANCIAL DOCUMENTS


NAME OF PROJECT. INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL PRING/REF IND MG-A5M22-166INFRA2022-AG5-052

Section IX. Checklist of Technical and Financial Documents

PR NO./REF. NO. MG-A5M22-165/NFRA2022-AG5-052

Checklist of Technical and Financial Documents

I. TECHNICAL COMPONENT ENVELOPE/Submit in three (3) copies- one (1) marked Original with the understanding that the Pass/Fail evaluation will be based only on the copy marked "Original"]



PR NO /REF NO MG-A5M22-165INFRA2022-AG5-052

FINANCIAL DOGE	IMEN.IS
~	contract to be bid, with their complete qualification and experience data, using NPC-MinGen Standard Form No. NPCMGNSF-INFR-05, 6a, 6b & 07; c. List of contractor's major equipment units, which are owned, leased, and/or under purchase agreements, supported by proof of ownership or certification of availability of equipment from the equipment lessor/vendor for the duration of the project, as the case may be, using NPC-MinGen Standard Form No. NPCMGNSF-INFR-08 and its
✓ (g)	supporting documents: and Original duly signed Omnibus Sworn Statement (OSS), using any of the following NPC-MinGen Standard Forms No.: NPCMGNSF-INFR-09a – for Sole Proprietorship; or NPCMGNSF-INFR-09b – for Partnership/Cooperative/Corporation/
	Joint Venture with the following supporting documents:
	and if applicable, Original Notarized Secretary's Certificate in case of a corporation, partnership, or cooperative; or Original Special Power of Attorney of all members of the joint venture giving full power and authority to its officer to sign the OSS and do acts to represent the Bidder.
Financia	d Documents
(h)	The prospective bidder's computation of Net Financial Contracting Capacity (NFCC)using NPC-MinGen Standard Form No. NPCMGNSF-INFR-10.
(i)	Class "B" Documents If applicable, duly signed joint venture agreement (JVA) in accordance with RA No. 4566 and its IRR in case the joint venture is already in existence, using NPC-MinGen Standard Form No. NPCMGNSF-INFR-11: or duly notarized statements from all the potential joint venture partners stating
	that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful.
marked O	IAL COMPONENT ENVELOPE [Submit in three (3) copies- one (1) briginal with the understanding that the Pass/Fail evaluation will be you on the copy marked "Original"]
(j)	Original of duly signed (each and every page) and accomplished Financial Bid Form, using NPC-MinGen Standard Form No. NPCMGNSF-INFR-12;
Other doo	 and cumentary requirements under RA No. 9184 Original of duly signed (each and every page) Bid Prices in the Bill of Quantities. using given form in Section VIII;

Duly signed (each and every page) and accomplished Detailed Estimates

Formusing NPC-MinGen Standard Form No. NPCMGNSF-INFR-13, including a summary sheet indicating the unit prices of construction materials, labor rates, and equipment rentals used in coming up with the Bidusing NPC form NPCMGNSF-INFR-14; and

(m) Cash Flow by Quarter or Month, as applicable (duly signed each and every page)

SECTION IX- CHECKLIST OF TECHNICAL &

FINANCIAL DOCUMENTS

HYDROTOR FANK FOR USED OIL PR NO./REF NO MG-A5M22-165INFRA2022-AG5-052

STANDARD BIDDING FORMS NPC-MINDANAO GENERATION

	1,3.1	C-MINDANAO GENERATION
NPCMGNSF-INFR-01	-	List of all Ongoing Government & Private Construction Contracts Including Contracts Awarded but not yet Started
NPCMGNSF-INFR-02	-	Statement of the Bidder's Single Largest Completed Contract (SLCC) similar to the contract to be bid
NPCMGNSF-INFR-03a	-	Form of Bid Security : Surety Bond
NPCMGNSF-INFR-03b	-	Bid Securing Declaration Form
NPCMGNSF-INFR-04	-:	Contractor's Organizational Chart for the Project
NPCMGNSF-INFR-05	=-	List of Key Personnel Proposed to be Assigned to the Project
NPCMGNSF-INFR-6a	•	Key Personnel's Certificate of Employment (Professional Personnel)
NPCMGNSF-INFR-6b	-	Key Personnel's Certificate of Employment (Construction Safety and Health Practitioner)
NPCMGNSF-INFR-07	-	Key Personnel's Bio-Data
NPCMGNSF-INFR-08	:-	List of Equipment, Owned or Leased and/or under Purchase Agreement, Pledged to the Proposed Project
NPCMGNSF-INFR-09a	:=	Omnibus Sworn Statement (Sole Proprietorship)
NPCMGNSF-INFR-09b	-	Omnibus Sworn Statement (Partnership/ Cooperative/Corporation//Joint Venture)
NPCMGNSF-INFR-10	-	Computation of Net Financial Contracting Capacity (NFCC)
NPCMGNSF-INFR-11	-	Joint Venture Agreement
NPCMGNSF-INFR-12	5.	Bid Form
NPCMGNSF-INFR-13	¥	Detailed Cost Estimate Form
NPCMGNSF-INFR-14	•	Summary Sheets of Materials Prices, Labor Rates

and Equipment Rental Rates

BID DOCUMENTS

Date

NAME OF PROJECT INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL

SECTION IX- CHECKLIST OF TECHNICAL &

PRIND/REF NO MG-A5M22-165INFRA2022-AG5-052

FINANCIAL DOCUMENTS				
Standard Form Number : NPC	MGNSF-INFR-01			
List of All (Ongoing Governm	ent and Private Co	nstruction Contracts	including
Name of Contract/Location/	a. Owner's Name		Contractor's Rol	e
Project Cost	b. Address c. Telephone Nos.	Nature of Work	Description	%
Government				
Private				
			~	
The bidder shall declare in this fo agreement other than his current				
Note: This statement shall be	supported with Contro	ct and/or Notice of Awa	rd (to be presented by the	winning bid
Submitted by :	(Printed Name & Sign	rature)		
Designation :				

BID DOCUMENTS

Submitted by

Designation Date NAME OF PROJECT. INSTALLATION OF CYLINDRICAL

HYDROTOR TANK FOR USED OIL

SECTION IX- CHECKLIST OF TECHNICAL &

FINANCIAL DOCUMENTS

PR NO./REF. NO. MG-A5M22-165INERA2022-AG5-052

The S	tatement of the Bidder	's Single Largest Comp	leted Contract	(SLCC
Business Name : Business Address :		 -		
	a. Owner's Name		Contracto	r's Role
Name of Contract	b. Address c. Telephone Nos.	Nature of Work	Description	%
				,
Note: The bidder must st shall be supported	ate only one (1) Single Largest with:	Completed Contract (SLCC)	similar to the cont	act to t
Contract and Notice Certificate of Com				

(Printed Name & Signature)

the private sector, an equivalent document (Ex. Official Receipt) shall be accepted.

Standard Form No. NPCMGNSF-INFR-03a

FORM OF BID SECURITY (SURETY BOND)

BOND	NO.:	DATE B	OND EXECUTED	D:	
and _ transa sum o demar	(Name of Surety ct business in the f <u>famount in wor</u> nd, for the paymen bind ourselves,	ame of Bidder)) of(Philippines (hereinds & figures as pretof which sum, welcour successors and	Name of Country nafter called "the escribed in the bid I and truly to be r	of Surely) Employer") as Iding document Inade, we, the s	, authorized to s Obligee, in the ts], callable or aid Principal and
SEALE	ED with our seals a	and dated this	day of	20	
	2	I has submitted a v D, for the			
NOW	THEREFORE, the	conditions of this o	bligation are:		
1)	If the Bidder wit Bidding Documen	hdraws his Bid du	iring the period	of bid validity	specified in the
2)		s not accept the co the instructions to E		netical errors o	f his bid price in

certificate within the prescribed period; or

4) If the bidder having been notified of the acceptance of his bid and award of contract to him by the Entity during the period of bid validity:

 If the Bidder, having determined as the LCB, fails or refuses to submit the required tax clearance, latest income and business tax returns and PhilGEPS registration

- a) Fails or refuses to execute the Contact; or
- b) Fails or refuses to submit the required valid JVA, if applicable; or
- Fails or refuses to furnish the Performance Security in accordance with the Instruction to Bidders;

Then this obligation shall remain in full force and effect, otherwise it shall be null and void.

PROVIDED HOWEVER, that the Surety shall not be:

- a) Liable for a grater sum than the specified penalty of this bond, nor
- b) Liable for a greater sum that the difference between the amount of the said Principal's Bid and the amount of the Bid that is accepted by the Employer.

BID DOCUMENTS

NAME OF PROJECT INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL PR NO./REF NO. MG-A5M22-166INFRA2022-AG5-052

SECTION IX- CHECKLIST OF TECHNICAL & FINANCIAL DOCUMENTS

Standard Form No: NPCMGNSF-INFR-03a

Page 2 of 2

This Surety executing this instrument hereby agrees that its obligation shall be valid for 120 calendar days after the deadline for submission of Bids as such deadline is stated in the Instructions to Bidders or as it may be extended by the Employer, notice of which extension(s) to the Surety is hereby waived.

PRINCIPAL	SURETY
SIGNATURE(S)	SIGNATURE(S)
NAME(S) AND TITLE (S)	NAME(S)
SEAL	SEAL

PR NO /REF NO MG-A5M22-165INFRA2022-AG5-052

BID SECURING DECLARATION Project Identification No.: [Insert number]

To: [Insert name and address of the Procuring Entity]

I/We, the undersigned, declare that:

- I/We understand that, according to your conditions, bids must be supported by a Bid Security, which may be in the form of a Bid Securing Declaration.
- 2. I/We accept that: (a) I/we will be automatically disqualified from bidding for any procurement contract with any procuring entity for a period of two (2) years upon receipt of your Blacklisting Order; and, (b) I/we will pay the applicable fine provided under Section 6 of the Guidelines on the Use of Bid Securing Declaration, within fifteen (15) days from receipt of the written demand by the procuring entity for the commission of acts resulting to the enforcement of the bid securing declaration under Sections 23.1(b), 34.2, 40.1 and 69.1, except 69.1(f) of the IRR of RA No. 9184; without prejudice to other legal action the government may undertake.
- I/We understand that this Bid Securing Declaration shall cease to be valid on the following circumstances:
 - Upon expiration of the bid validity period, or any extension thereof pursuant to your request;
 - b. I am/we are declared ineligible or post-disqualified upon receipt of your notice to such effect, and (i) I/we failed to timely file a request for reconsideration or (ii) I/we filed a waiver to avail of said right; and
 - c. I am/we are declared the bidder with the Lowest Calculated Responsive Bid, and I/we have furnished the performance security and signed the Contract.

IN WITNESS WHEREOF, I/We have hereunto set my/our hand/s this ____ day of [month] [year] at [place of execution].

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE]
[Insert signatory's legal capacity]

Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]

Standard Form No: NPCMGNSF-INFR-04

CONTRACTOR'S ORGANIZATIONAL CHART FOR THE CONTRACT

Submit Copy of the Organizational Chart that the Contractor intends to use to execute the Contract if awarded to him. Indicate in the chart the names of the Project Manager, Project Engineer, Foreman and other Key Engineering Personnel.

Attach the required Proposed Organizational Chart for the Contract as stated above

NOTES:

- 1. This organization chart should represent the "Contractor's Organization" required for the Project, and not the organizational chart of the entire firm.
- Each such nominated engineer/key personnel shall comply with and submit their complete qualification and experience data.
- 3. All these are required to be in the Technical Envelope of the Bidder.

BID DOCUMENTS

NAME OF PROJECT I INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL

SECTION IX- CHECKLIST OF TECHNICAL &

FINANCIAL DOCUMENTS

PR NO VREF NO MG-A5M22-165INFRA2022-AG5-052

Standard Form Number: NPCMGNSF-INFR-05

LIST OF KEY PERSONNEL PROPOSED TO BE ASSIGNED TO THE CONTRACT (Based on the Minimum Key Personnel Required in the Bidding Documents)

Business Name :					
Division by :					
business :					
			DESIGNATION		
1. Name					
2. Address		1			
3. Date of Birth	7	1)		
4. Employed Since		1			l:
5. Experience					
6. Previous Employment		1			
7. Education					
8. PRC License					
Water State of the					
Required Attachments during Postqualification:					
1 Valid PRC License of the (professional) personnel)					
Certificate of Training with accreditation from DOLE of ti	re Construction Safety and He	alth Officer			
 TESDA Training Certificate (NC II) of Welder or Electrican, 	whichever is applicable				
4 Copy of Diploma and/or Service Record/Certificate of Em	ployment of previous and/or c	urrent employer of Foreman	n, Welder, Plumber or Elec	trician, whichever is applica	ible
shall be submitted during post qualification by the winni					
Submitted by:					
	(Printed nam	ie & Signature)			
Designation:					
Date					
Date					

One of the requirements from the bidder to be included in its Technical Envelope is a list of contractor's key personnel (based on the minimum key personnel required in the bidding documents) to be assigned to the contract to be bid, with their complete qualification and experience data (including the key personnel's signed written commitment to work for the project once awarded the contract).

NAME OF PROJECT | INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL

SECTION IX- CHECKLIST OF TECHNICAL &

Standard Form No: NPCMGNSF-INFR-06a

FINANCIAL DOCUMENTS

PRING/REF NO. MG-A5M22-165INFRA2022-AG5-052

KEY PERSONNEL'S CERTIFICATE OF EMPLOYMENT (PROFESSIONAL PERSONNEL)

Issuance Date THE VICE PRESIDENT National Power Corporation Mindanao Generation Maria Cristina, Iligan City Dear Sir. (Name of Nominee) a Licensed Engineer with issued on Professional License No. at (date of issuance) (place of issuance) Has engaged my services as I hereby certify that (Name of Bidder) for the , if awarded to it. (Name of Project) (Designation) (Designation) , I supervised the following completed projects As Similar to the contract under bidding: DATE NAME OF PROJECT OWNER COST COMPLETED At present, I am supervising the following projects: DATE NAME OF PROJECT OWNER COST COMPLETED In case of my separation for any reason whatsoever from the above-mentioned Contractor, I shall notify the National Power Corporation at least twenty one (21) days before the effective date of separation. , I know I will have to stay in the job site (Designation) all the time to supervise and manage the Contract works to the best of my ability, and aware that I am authorized to handle only one (1) contract at a time.

One of the requirements from the bidder to be included in its Technical Envelope is a list of contractor's key personnel (viz Project Manager, Project Engineer, Safety & Health Practitioner, Foremen, etc.), to be assigned to the contract to be bid, with their complete qualification and experience data (including the key personnel's signed written commitment to work for the project once awarded the contract).

NAME OF PROJECT. INSTALLATION OF CYLINDRICAL HYDROLOR TANK FOR USED DIE

SECTION IX- CHECKLIST OF TECHNICAL & FINANCIAL DOCUMENTS

PRING /REF NO. MG-A5M22-165INFRA2022-AG5-052

Standard Form No: NPCMGNSF-INFR-06a

Page 2 of 2

I do not allow the use of my name for the purpose of Contractor to qualify for the Contract without any firm common post of (Designation) therefore, if the contract understand that to do so will be a sufficient group (Designation) in any future National employment with any Contractor doing business with the National	nitment on my part to assume the ntract is awarded to him since I nd for my disqualification as Power Corporation bidding or
	(Name and Signature)
	AFFIANT
REPUBLIC OF THE PHILIPPINES)	
City/Municipality of)S.S.	
SUBSCRIBED AND SWORN TO before me this affiant exhibiting to me his/her Community Tax Certificated at at, Philippines.	, day of20, e Noissued on
	Notary Public Until 31 December 20 PTR No.
	Until 31 December 20 PTR No. Issued at:
	Until 31 December 20 PTR No.
	Until 31 December 20 PTR No. Issued at: Issued on:

One of the requirements from the bidder to be included in its Technical Envelope is a list of contractor's key personnel (viz. Project Manager, Project Engineer, Safety & Health Practitioner, Foremen, etc.), to be assigned to the contract to be bid, with their complete qualification, and experience data (including the key personnel's signed written commitment to work for the project once awarded the contract)

Standard Form No: NPCMGNSF-INFR-06b

NAME OF PROJECT INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL PRINO/REF NO. MG-A5M22-165INFRA2022-AG5-052

SECTION IX- CHECKLIST OF TECHNICAL & FINANCIAL DOCUMENTS

KEY PERSONNEL'S CERTIFICATE OF EMPLOYMENT (CONSTRUCTION SAFETY AND HEALTH PRACTITIONER)

THE VICE PRESIDENT National Power Corporation Mindanao Generation Maria Cristina, Iligan City		=	Issuance Date
Dear Sir.			
I am (Name of Nomin			Engineer with
Professional License No.	Issued on		at issuance) (place
of issuance)		_,	——————————————————————————————————————
I hereby certify that(N	ame of Bidder)	На	as engaged my services as
(Designation)	for the (Name of F	roject)	, if awarded to it.
As (Designation) Similar to the contract under bid		vised the fol	lowing completed projects
NAME OF PROJECT	OWNER	COST	DATE COMPLETED
At present, I am supervis	ing the following project	s: COST	DATE COMPLETED
In case of my separation Contractor, I shall notify the National Separation Contractor, I shall notify the National Separation Contractor, I shall notify the National Separation Contractor of the Separation Contractor o	ational Power Corporat		

As Safety and Health Practitioner, I know I will have to stay in the job site all the time and aware that I am authorized to handle only one (1) contract at a time.

One of the requirements from the bidder to be included in its Technical Envelope is a list of contractor's key personnel (viz. Project Manager, Project Engineer, Safety & Health Practitioner, Foremen, etc.), to be assigned to the contract to be bid, with their complete qualification and experience data (including the key personnel's signed written commitment to work for the project once awarded the contract).

NAME OF PROJECT INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL

SECTION IX- CHECKLIST OF TECHNICAL & FINANCIAL DOCUMENTS

PR NO /REF NO MG-A5M22-165INFRA2022-AG5-052

Standard Form No: NPCMGNSF-INFR-06b Page 2 of 2

I do not allow the use of my name for the purpose of enabling the above-mentioned Contractor to qualify for the Contract without any firm commitment on my part to assume the post of Safety and Health Practitioner, if the contract is awarded to him since I understand that to do so will be a sufficient ground for my disqualification as Safety and Health Practitioner in any future National Power Corporation bidding or employment with any Contractor doing business with the National Power Corporation.

	(Name and Signature) AFFIANT
REPUBLIC OF THE PHILIPPINES) City/Municipality of	
SUBSCRIBED AND SWORN TO before me th affiant exhibiting to me his/her Community Tax Certific at, Philippines.	nis, day of20, ate Noissued on
	Notary Public Until 31 December 20 PTR No. Issued at: Issued on: TIN No.
Doc. No. Page No. Book No. Series of	

One of the requirements from the bidder to be included in its Technical Envelope is a list of contractor's key personnel (viz Project Manager, Project Engineer, Safety & Health Practitioner, Foremen, etc.), to be assigned to the contract to be bid, with their complete qualification and experience data (including the key personnel's signed written commitment to work for the project once awarded the contract).

ICAL & PR NO./REF NO. MG-A5M22-165INFRA2022-AG5-052

Standard Form No: NPCMGNSF-INFR-07

KEY PERSONNEL (FORMAT OF BIO-DATA)

Give the detailed information of the following personnel who are scheduled to be assigned as full-time staff for the project. Fill up a form for each person.

1.	Name	:			
2.	Date of Birth	1			
3.	Nationality	;			
4.	Education and Degrees	\$.			
5.	Specialty	1			
6.	Registration	:			
7.	Length of Service with the	-	Year		
	Firm	*	from	(months)	(year)
			To	(months)	(year)
8.	Years of Experience				
9.	If item 7 is less than the req Clause 10.4, give name and the required number of years additional sheet/s), if necessa	length of exp	of service with p	revious employ	ers to satisfy
	Name and Address of Employ	<u>er</u>	Ī	Length of Service	
			Υe	ar(s) from	to
			Ye	ear(s) from	to
		-	Ye	ear(s) from	to

10. Experience:

This should cover the past ten (10) years of experience. (Attached as many pages as necessary to show involvement of personnel in projects using the format below).

One of the requirements from the bidder to be included in its Technical Envelope is a list of contractor's key personnel (viz Project Manager Project Engineer, Safety & Health Practitioner, Foremen, etc.), to be assigned to the contract to be bid, with their complete qualification and experience data (including the key personnel's signed written commitment to work for the project once awarded the contract):

BID DOCUMENTS

SECTION IX- CHECKLIST OF TECHNICAL & FINANCIAL DOCUMENTS

NAME OF PROJECT INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL PR NO./REF NO. MG-A5M22-165INFRA2022-AG5-052

Standard Form No: NPCMGNSF-INFR-07 Page 2 of 2

1.	Name	:			
2.	Name and Address of Owner	:			
	Name and Address of the Owner's Engineer (Consultant) Indicate the Features of Project	:			
	(particulars of the project components and any other particular interest connected with the project)				
5.	Contract Amount Expressed in Philippine Currency	1			
6.	Position	3	 		
7.	Structures for which the employee was responsible				
8.	Assignment Period	:	from	(months)	(years)
			to	(months)	(years)
	Name and Signature of				
	Employee				
	hereby certified that the above person irded to our company.	ne	can be assigned to	this project, if the	contract is
	(Place and Date)		(The Auth	orized Represer	rtative)

One of the requirements from the bidder to be included in its Technical Envelope is a list of contractor's key personnel (viz. Project Manager, Project Engineer, Safety & Health Practitioner, Foremen, etc.), to be assigned to the contract to be bid, with their complete qualification and experience data (including the key personnel's signed written commitment to work for the project.

Once awarded the contract).

BID DOCUMENTS

NAME OF PROJECT. INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL

SECTION IX- CHECKLIST OF TECHNICAL &

FINANCIAL DOCUMENTS

PR NO /REF. NO MG-A5M22 165INFRA2022-AG5 052

Standard Form Number: NPCMGNSF-INFR - 08

LIST OF EQUIPMENT, OWNED OR LEASED AND/OR UNDER PI (Based on the Minimum Equipment Required in the Bio

Description	Model/Year	Capacity/ Performance / Size	Plate No.	Motor No. / Body No.	
A. Owned					
At					_
к. Б.					_
IIIi					L
W.					L
B. Leased					_
					L
ii,					L
iiI.					L
iv.					L
C. Under Purchased Agreeme	nts				
s	=-				L
(f).				_	L
(i).					L
V.		<u> </u>			L
V:	Submitted by				1
	Del SMELLY		(Pi	ninted name & Signature)	Γ
	Designation	:			
	Date				

One of the requirements from the bidder to be included in its Technical Envelope is the list of its equipment units pledged for the control which are owned (supported by proof/s of ownership), leased, and/or under purchase agreements (with corresponding engine numbers, availability of equipment from the equipment lessor/vendor for the duration of the project.

PR NO /REF NO. MG-A5M22-165INFRA2022-AG5-052

Standard Form No: NPCMGNSF-INFR-09a

Omnibus Sworn Statement (Revised)

(SOLE PROPRIETORSHIP)

REPUBLIC OF THE PHILIPPINES)
CITY/MUNICIPALITY OF	S.S

AFFIDAVIT

I,[Name of Affiant], of legal age, [Civil Status], [Nationality], and residing at [Address of Affiant], after having been duly sworn in accordance with law, do hereby depose and state that:

- I am the sole proprietor or authorized representative of [Name of Bidder] with office address at [address of Bidder];
- As the owner and sole proprietor, or authorized representative of [Name of Bidder], I
 have full power and authority to do, execute and perform any and all acts necessary to
 participate, submit the bid, and to sign and execute the ensuing contract for [Name of the
 Project] of the National Power Corporation-Mindanao Generation, as shown in the
 attached duly notarized Special Power of Attorney;
- 3. [Name of Bidder] is not "blacklisted" or barred from bidding by the Government of the Philippines or any of its agencies, offices, corporations, or Local Government Units, foreign government/foreign or international financing institution whose blacklisting rules have been recognized by the Government Procurement Policy Board, by itself or by relation, membership, association, affiliation, or controlling interest with another blacklisted person or entity as defined and provided for in the Uniform Guidelines on Blacklisting;
- Each of the documents submitted in satisfaction of the bidding requirements is an authentic copy of the original, complete, and all statements and information provided therein are true and correct;
- [Name of Bidder] is authorizing the Head of the Procuring Entity or its duly authorized representative(s) to verify all the documents submitted;
- 6. The owner or sole proprietor is not related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;
- 7. [Name of Bidder] complies with existing labor laws and standards; and
- [Name of Bidder] is aware of and has undertaken the responsibilities as a Bidder in compliance with the Philippine Bidding Documents, which includes:
 - a. Carefully examining all of the Bidding Documents;
 - Acknowledging all conditions, local or otherwise, affecting the implementation of the Contract;

NAME OF PROJECT. INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED TILL

SECTION IX- CHECKLIST OF TECHNICAL & FINANCIAL DOCUMENTS

PR NO /REF NO MG-A5M22-165INFRA2022-AG5-052

Standard Form No: NPCMGNSF-INFR-09a

Page 2 of 2

- Making an estimate of the facilities available and needed for the contract to be bid, if any; and
- Inquiring or securing Supplemental/Bid Bulletin(s) issued for the [Name of the Project].
- [Name of Bidder] did not give or pay directly or indirectly, any commission, amount, fee, or any form of consideration, pecuniary or otherwise, to any person or official, personnel or representative of the government in relation to any procurement project or activity.
- 10. In case advance payment was made or given, failure to perform or deliver any of the obligations and undertakings in the contract shall be sufficient grounds to constitute criminal liability for Swindling (Estafa) or the commission of fraud with unfaithfulness or abuse of confidence through misappropriating or converting any payment received by a person or entity under an obligation involving the duty to deliver certain goods or services, to the prejudice of the public and the government of the Philippines pursuant to Article 315 of Act No. 3815 s. 1930, as amended, or the Revised Penal Code.

IN	WITNESS	WHEREOF,	10	have	hereunto	set	my	hand	this	_	day	of	 20	at
_		_, Philippines.					-							

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE]
[Insert signatory's legal capacity]
Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]

PR NO./REF_NO_MG-A5M22-165INFRA2022-AG5-052

Standard Form No: NPCMGNSF-INFR-09b

Omnibus Sworn Statement (Revised) PARTNERSHIP/COOP/CORP/JOINT VENTURE

THE THE PARTY OF T

REPUBLIC OF THE PHILIPPIN	ES)
CITY/MUNICIPALITY OF) S.S.

AFFIDAVIT

I,[Name of Affiant], of legal age, [Civil Status], [Nationality], and residing at [Address of Affiant], after having been duly sworn in accordance with law, do hereby depose and state that:

- I am the duly authorized and designated representative of [Name of Bidder] with office address at [address of Bidder];
- I am granted full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for [Name of the Project] of the National Power Corporation-Mindanao Generation, as shown in the attached [state title of attached document showing proof of authorization (e.g., duly notarized Secretary's Certificate, Board/Partnership Resolution, or Special Power of Attorney, whichever is applicable;)];
- 3. [Name of Bidder] is not "blacklisted" or barred from bidding by the Government of the Philippines or any of its agencies, offices, corporations, or Local Government Units, foreign government/foreign or international financing institution whose blacklisting rules have been recognized by the Government Procurement Policy Board, by itself or by relation, membership, association, affiliation, or controlling interest with another blacklisted person or entity as defined and provided for in the Uniform Guidelines on Blacklisting;
- Each of the documents submitted in satisfaction of the bidding requirements is an authentic copy of the original, complete, and all statements and information provided therein are true and correct;
- [Name of Bidder] is authorizing the Head of the Procuring Entity or its duly authorized representative(s) to verify all the documents submitted;
- [If a partnership or cooperative:] None of the officers and members of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;
 - [If a corporation or joint venture:] None of the officers, directors, and controlling stockholders of [Name of Bidder] is related to the Head of the Procuring Entity, members of the Bids and Awards Committee (BAC), the Technical Working Group, and the BAC Secretariat, the head of the Project Management Office or the end-user unit, and the project consultants by consanguinity or affinity up to the third civil degree;

NAME OF PROJECT. INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL

SECTION IX- CHECKLIST OF TECHNICAL &

PRINO/REF NO: MG-A5M22-185INFRA2022-AG5-052

FINANCIAL DOCUMENTS

Standard Form No: NPCMGNSF-INFR-09b

Page 2 of 2

- [Name of Bidder]complies with existing labor laws and standards; and
- 8. [Name of Bidder] is aware of and has undertaken the responsibilities as a Bidder in compliance with the Philippine Bidding Documents, which includes:
 - Carefully examining all of the Bidding Documents;
 - b. Acknowledging all conditions, local or otherwise, affecting the implementation of the Contract:
 - Making an estimate of the facilities available and needed for the contract to be bid, if C. any; and
 - Inquiring or securing Supplemental/Bid Bulletin(s) issued for the [Name of the Project1.
- 9. [Name of Bidder] did not give or pay directly or indirectly, any commission, amount, fee, or any form of consideration, pecuniary or otherwise, to any person or official, personnel or representative of the government in relation to any procurement project or activity.
- 10. In case advance payment was made or given, failure to perform or deliver any of the obligations and undertakings in the contract shall be sufficient grounds to constitute criminal liability for Swindling (Estafa) or the commission of fraud with unfaithfulness or abuse of confidence through misappropriating or converting any payment received by a person or entity under an obligation involving the duty to deliver certain goods or services, to the prejudice of the public and the government of the Philippines pursuant to Article 315 of Act No. 3815 s. 1930, as amended, or the Revised Penal Code.

IN	WITNESS	WHEREOF.	have	hereunto	set	my	hand	this	_	day	of	 20	at
		_, Philippines.											

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE [Insert signatory's legal capacity] Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]

PR NO./REF NO MG-A5M22-185(NFRA2022-AG5-052

Standard Form No: NPCMGNSF-INFR-10

NET FINANCIAL CONTRACTING CAPACITY (NFCC)

A. Summary of the Bidder's/Contractor's assets and liabilities on the basis of the income tax return and audited financial statement for the immediately preceding calendar year are:

		Year 20
1.	Total Assets	
2.	Current Assets	
3.	Total Liabilities	
4.	Current Liabilities	
5.	Net Worth (1-3)	
6.	Net Working Capital (2-4)	

B. The Net Financial Contracting Capacity (NFCC) based on the above data is computed as follows:

NFCC = [(Current assets minus current liabilities) x 15] minus the value of all outstanding or uncompleted portions of the projects under ongoing contracts, including awarded contracts yet to be started coinciding with the contract for this Project.

Herewith attached is certified true copy of the audited financial statement, stamped "RECEIVED" by the BIR or BIR authorized collecting agent for the immediately preceding calendar year.

Name of Bidder/Contractor
Signature of Authorized Representative
Date:

Submitted by:

NAME OF PROJECT : INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL

SECTION IX- CHECKLIST OF TECHNICAL &

PR NO./REF NO. MG-A5M22-165INFRA2022-AG5-052

FINANCIAL DOCUMENTS

Standard Form No: NPCMGNSF-INFR-11

JOINT VENTURE AGREEMENT

KNOW ALL MEN BY THESE PRESENTS:									
, of legal a	EMENT is entered in to by and between: age, <u>(civil status)</u> , authorized representative of of								
	and -								
, of legal age, and a resident of	(civil status) authorized representative of								
resources and efforts to enable the Joint Ve	That both parties agree to join together their capital, manpower, equipment, and other esources and efforts to enable the Joint Venture to participate in the Bidding and Undertaking of the ereunder stated Contract of the National Power Corporation .								
NAME OF FIRM	NAME OF FIRM CAPITAL CONTRIBUTION								
That the capital contribution of each member firm:									
NAME OF FIRM	CAPITAL CONTRIBUTION								
ă. 9.	DHB								
That both parties agree to be jointly and Undertaking of the said contract.	y and severally liable for their participation in the Bidding								
That both parties agree that and/or shall be the Official Representative/s of the Joint Venture, and are granted full power and authority to do, execute and perform any and all acts necessary and/or to represent the Joint Venture in the Bidding and Undertaking of the said contract, as fully and effectively and the Joint Venture may do and if personally present with full power of substitution and revocation.									
That this Joint Venture Agreement shall remain in effect only for the above stated Contract until terminated by both parties.									
Name & Signature of Authorized Representative	Name & Signature of Authorized Representative								
Official Designation	Official Designation								
Name of Firm	Name of Firm								
	Witnesses								

If the bidder is a joint venture, one of the requirements is the submission of a valid joint venture agreement.

NAME OF PROJECT : INSTALLATION OF CYLINDRICAL HYDROTOR TANK FOR USED OIL PR NO./REF NO. MG-A6M22-165INFRA2022-AG5-052

SECTION IX- CHECKLIST OF TECHNICAL &

FINANCIAL DOCUMENTS

Standard Form No: NPCMGNSF-INFR-11

Page 2 of 2

ACKNOWLEDGEMENT

BEFORE ME, a Notary Public for and in	, Philippines, this day of
, 20 personally appeared	, authorized
representative, of with	* · · · · · · · · · · · · · · · · · · ·
, issued at,	on, AND
authorized representa	
	issued at, on
Known to me to be the same	person who executed the foregoing
instrument consisting of two (2) pages, including the page written, all pages signed by both parties and the	eir instrumental witnesses and they
acknowledged before me that the same are their free at	
of the Corporations they represents.	
and the second s	
WITNESS MY HAND AND NOTARIAL SEAL, at	the place and on the date first
above written.	
	Notary Public
	Until 31 December 20
	PTR No.
	Issued at
	Issued on:
	TIN No.
Doc. No.	
Page No.	
Book No.	
Series of	

If the bidder is a joint venture, one of the requirements is the submission of a valid joint venture agreement Standard Form No: NPCMGNSF-INFR-12

Bid Form for the Procurement of Infrastructure Projects

		BID FORM		
			Date :	
Proje	ct Identification No. :			
To:	The Vice President			
	National Power Corporation			
	Mindanao Generation			
	Maria Cristina, Iligan City			

Having examined the Philippine Bidding Documents (PBDs) including the Supplemental or Bid Bulletin Numbers [insert numbers], the receipt of which is hereby duly acknowledged, we, the undersigned, declare that:

- a. We have no reservation to the PBDs, including the Supplemental or Bid Bulletins, for the Procurement Project: [insert name of contract]:
- b. We offer to execute the Works for this Contract in accordance with the PBDs:
- c. The total price of our Bid in words and figures, excluding any discounts offered below is: [insert information];
- d. The discounts offered and the methodology for their application are: [insert information];
- e. The total bid price includes the cost of all taxes, such as, but not limited to: [specify the applicable taxes, e.g. (i) value added tax (VAT), (ii) income tax, (iii) local taxes, and (iv) other fiscal levies and duties], which are itemized herein and reflected in the detailed estimates.
- f. Our Bid shall be valid within the a period stated in the PBDs, and it shall remain binding upon us at any time before the expiration of that period;
- g. If our Bid is accepted, we commit to obtain a Performance Security in the amount of <u>[insert percentage amount]</u>percent of the Contract Price for the due performance of the Contract, or a Performance Securing Declaration in lieu of the the allowable forms of Performance Security, subject to the terms and conditions of issued GPPB guidelines¹ for this purpose;
- We are not participating, as Bidders, in more than one Bid in this bidding process, other than alternative offers in accordance with the Bidding Documents;
- We understand that this Bid, together with your written acceptance thereof included in your notification of award, shall constitute a binding contract between us, until a formal Contract is prepared and executed; and

Standard Form No: NPCMGNSF-INFR-12

Page 2 of 2

eurrently based on GPPB Resolution No. 09-2020

PR NO./REF. NO. MG-A5M22-165INFRA2022-AG5-052

- We understand that you are not bound to accept the Lowest Calculated Bid or any other Bid that you may receive.
- k. We likewise certify/confirm that the undersigned, is the duly authorized representative of the bidder, and granted full power and authority to do, execute and perform any and all acts necessary to participate, submit the bid, and to sign and execute the ensuing contract for the [Name of Project] of the National Power Corporation-Mindanao Generation.
- We acknowledge that failure to sign each and every page of this Bid Form, including the Bill of Quantities, shall be a ground for the rejection of our bid.

Name:	
Legal Capacity:	
Signature:	
Duly authorized to sign the Bid for and behalf of:	
Date:	

BI	ГΔ	D	TM	Till	iN	IF!	N	S
D1		100	534		NV	ш	M	

NAME OF PROJECT. INSTALLATION OF CYLINDRICAL

HYDROTOR TANK FOR USED OIL

SECTION IX- CHECKLIST OF TECHNICAL &

FINANCIAL DOCUMENTS

PRINO//REF NO MG-A5M22-165INFRA2022-AG5-952

standard	Form Number	: NPCMGNSF-	INFR - 13

DETAILED COST ESTIMATE FORM

Name of Bidde:		
_		

Item No.	ii	Unit of	Direct Cost		Mar	k-Up	
nem No.	Item Description	Measure	Materials	Labor	Equipment	OCM	P
		4		,41			ļ
				ļ			<u> </u>
					ļ		<u> </u>
				·	<u> </u>		
		<u> </u>		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			ļ
		1			ļļ.		ļ
		1			-		<u> </u>
		1					ļ
		1					!
		+					_
		+			L		<u> </u>
		4					<u> </u>
		1			<u> </u>		↓
		+		ļ	{		<u>ļ</u>
				ļ	ļ <u> </u>		-
		1 1					_
		1		.			<u> </u>
							1

Name, Signature of Authorized Representative

PR NO./REF. NO MG-A5M22-165/INFRA2022-AG5-052

Standard Form No: NPCMGNSF-INFR-14

SUMMARY SHEETS OF MATERIALS PRICES, LABOR RATES AND EQUIPMENT RENTAL RATES

Nam	ne of Bidder:		
ı.	Unit Prices of Materials		
	Materials Description	Unit	Unit Price
n.	Manpower Hourly Rates		
	Designation	Rate/Hr.	
	Wo	rki	
III.	Equipment Hourly Rental Rates		
	Equipment Description	Rental Rate/Hr.	
Nai	me, Signature of Authorized Representative	Design	ation

Performance Securing Declaration (Revised)

[if used as an alternative performance security but it is not required to be submitted with the Bid, as it shall be submitted within ten (10) days after receiving the Notice of Award]

REPUBLIC OF THE PHILIPPINES)	
CITY OF)	S.S.

PERFORMANCE SECURING DECLARATION

Invitation to Bid: [Insert Reference Number indicated in the Bidding Documents] To: [Insert name and address of the Procuring Entity]

I/We, the undersigned, declare that:

- I/We understand that, according to your conditions, to guarantee the faithful
 performance by the supplier/distributor/manufacturer/contractor/consultant of its
 obligations under the Contract, I/we shall submit a Performance Securing Declaration
 within a maximum period of ten (10) calendar days from the receipt of the Notice of
 Award prior to the signing of the Contract.
- I/We accept that: I/we will be automatically disqualified from bidding for any
 procurement contract with any procuring entity for a period of one (1) year for the first
 offense, or two (2) years for the second offense, upon receipt of your Blacklisting
 Order if I/We have violated my/our obligations under the Contract;
- I/We understand that this Performance Securing Declaration shall cease to be valid upon.
 - a. issuance by the Procuring Entity of the Certificate of Final Acceptance, subject to the following conditions:
 - Procuring Entity has no claims filed against the contract awardee;
 - ii. It has no claims for labor and materials filed against the contractor; and
 - iii. Other terms of the contract: or
 - b. replacement by the winning bidder of the submitted PSD with a performance security in any of the prescribed forms under Section 39.2 of the 2016 revised IRR of RA No. 9184 as required by the end-user.

IN WITNESS WHEREOF, I/We have hereunto set my/our hand/s this ____ day of [month] [year] at [place of execution].

[Insert NAME OF BIDDER OR ITS AUTHORIZED REPRESENTATIVE] [Insert signatory's legal capacity] Affiant

[Jurat]

[Format shall be based on the latest Rules on Notarial Practice]

Contract Agreement Form for the Procurement of Infrastructure Projects (Revised)

[not required to be submitted with the Bid, but it shall be submitted within ten (10) days after receiving the Notice of Award]

CONTRACT AGREEMENT

THIS AGREEMENT, made this [insert date] day of [insert month], [insert year] between [name and address of PROCURING ENTITY] (hereinafter called the "Entity") and [name and address of Contractor] (hereinafter called the "Contractor").

WHEREAS, the Entity is desirous that the Contractor execute [name and identification number of contract] (hereinafter called "the Works") and the Entity has accepted the Bid for [contract price in words and figures in specified currency] by the Contractor for the execution and completion of such Works and the remedying of any defects therein.

NOW THIS AGREEMENT WITNESSETH AS FOLLOWS:

- In this Agreement, words and expressions shall have the same meanings as are respectively assigned to them in the Conditions of Contract hereinafter referred to.
- The following documents as required by the 2016 revised Implementing Rules and Regulations of Republic Act No. 9184 shall be deemed to form and be read and construed as part of this Agreement, viz.:
 - a. Philippine Bidding Documents (PBDs);
 - Drawings/Plans;
 - ii. Specifications:
 - iii. Bill of Quantities:
 - iv. General and Special Conditions of Contract;
 - v. Supplemental or Bid Bulletins, if any;
 - Winning bidder's bid, including the Eligibility requirements, Technical and Financial Proposals, and all other documents or statements submitted;

Bid form, including all the documents/statements contained in the Bidder's bidding envelopes, as annexes, and all other documents submitted (e.g., Bidder's response to request for clarifications on the bid), including corrections to the bid, if any, resulting from the Procuring Entity's bid evaluation:

- c. Performance Security;
- d. Notice of Award of Contract and the Bidder's conforme thereto; and
- e. Other contract documents that may be required by existing laws and/or the Procuring Entity concerned in the PBDs. Winning bidder agrees that additional contract documents or information prescribed by the GPPB that are subsequently required for submission after the contract execution, such as the Notice to Proceed, Variation Orders, and Warranty Security, shall likewise form part of the Contract.

PR NO /REF NO MG-A5M22-165/INFRA2022-AG5-052

- In consideration for the sum of [total contract price in words and figures] or such
 other sums as may be ascertained, [Named of the bidder] agrees to [state the
 object of the contract] in accordance with his/her/its Bid.
- The [Name of the procuring entity] agrees to pay the above-mentioned sum in accordance with the terms of the Bidding.

IN WITNESS whereof the parties thereto have caused this Agreement to be executed the day and year first before written.

[Insert Name and Signature]

[Insert Name and Signature]

[Insert Signatory's Legal Capacity]

[Insert Signatory's Legal Capacity]

for:

for.

[Insert Procuring Entity]

[Insert Name of Supplier]

Acknowledgment

[Format shall be based on the latest Rules on Notarial Practice]

g Draft

